JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class Pipe

java.lang.Object
    java.nio.channels.Pipe

```
public abstract class Pipe
extends Object
```

A pair of channels that implements a unidirectional pipe.

A pipe consists of a pair of channels: A writable `sink` channel and a readable `source` channel. Once some bytes are written to the sink channel they can be read from the source channel in exactly the order in which they were written.

Whether or not a thread writing bytes to a pipe will block until another thread reads those bytes, or some previously-written bytes, from the pipe is system-dependent and therefore unspecified. Many pipe implementations will buffer up to a certain number of bytes between the sink and source channels, but such buffering should not be assumed.

Since:

1.4

Nested Class Summary

Nested Classes

Modifier and Type	Class	Description
`static class`	`Pipe.SinkChannel`	A channel representing the writable end of a `Pipe`.
`static class`	`Pipe.SourceChannel`	A channel representing the readable end of a `Pipe`.

Constructor Summary

Constructors

Modifier	Constructor	Description
`protected`	`Pipe()`	Initializes a new instance of this class.

Method Summary

All Methods	Static Methods	

Modifier and Type	Method	Description
static Pipe	open()	Opens a pipe.
abstract Pipe.SinkChannel	sink()	Returns this pipe's sink channel.
abstract Pipe.SourceChannel	source()	Returns this pipe's source channel.

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

Pipe

```
protected Pipe()
```

Initializes a new instance of this class.

Method Details

source

```
public abstract Pipe.SourceChannel source()
```

Returns this pipe's source channel.

Returns:

This pipe's source channel

sink

```
public abstract Pipe.SinkChannel sink()
```

Returns this pipe's sink channel.

Returns:

This pipe's sink channel

open

```
public static Pipe open()
                throws IOException
```

Opens a pipe.

The new pipe is created by invoking the `openPipe` method of the system-wide default `SelectorProvider` object.

Returns:

A new pipe

Throws:

`IOException` - If an I/O error occurs

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.