JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface ReadableByteChannel

All Superinterfaces:

AutoCloseable, Channel, Closeable

All Known Subinterfaces:

ByteChannel, ScatteringByteChannel, SeekableByteChannel

All Known Implementing Classes:

DatagramChannel, FileChannel, Pipe.SourceChannel, SocketChannel

---

```
public interface ReadableByteChannel
extends Channel
```

A channel that can read bytes.

Only one read operation upon a readable channel may be in progress at any given time. If one thread initiates a read operation upon a channel then any other thread that attempts to initiate another read operation will block until the first operation is complete. Whether or not other kinds of I/O operations may proceed concurrently with a read operation depends upon the type of the channel.

Since:

1.4

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
int	**read**(ByteBuffer dst)	Reads a sequence of bytes from this channel into the given buffer.

Methods declared in interface Channel

close, isOpen

Method Details

read

```
int read(ByteBuffer dst)
  throws IOException
```

Reads a sequence of bytes from this channel into the given buffer.

An attempt is made to read up to *r* bytes from the channel, where *r* is the number of bytes remaining in the buffer, that is, `dst.remaining()`, at the moment this method is invoked.

Suppose that a byte sequence of length *n* is read, where `0` <= *n* <= *r*. This byte sequence will be transferred into the buffer so that the first byte in the sequence is at index *p* and the last byte is at index *p* + *n* - `1`, where *p* is the buffer's position at the moment this method is invoked. Upon return the buffer's position will be equal to *p* + *n*; its limit will not have changed.

A read operation might not fill the buffer, and in fact it might not read any bytes at all. Whether or not it does so depends upon the nature and state of the channel. A socket channel in non-blocking mode, for example, cannot read any more bytes than are immediately available from the socket's input buffer; similarly, a file channel cannot read any more bytes than remain in the file. It is guaranteed, however, that if a channel is in blocking mode and there is at least one byte remaining in the buffer then this method will block until at least one byte is read.

This method may be invoked at any time. If another thread has already initiated a read operation upon this channel, however, then an invocation of this method will block until the first operation is complete.

Parameters:

`dst` - The buffer into which bytes are to be transferred

Returns:

The number of bytes read, possibly zero, or `-1` if the channel has reached end-of-stream

Throws:

`IllegalArgumentException` - If the buffer is read-only

`NonReadableChannelException` - If this channel was not opened for reading

`ClosedChannelException` - If this channel is closed

`AsynchronousCloseException` - If another thread closes this channel while the read operation is in progress

`ClosedByInterruptException` - If another thread interrupts the current thread while the read operation is in progress, thereby closing the channel and setting the current thread's interrupted status

`IOException` - If some other I/O error occurs

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.