JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class CodingErrorAction

java.lang.Object
    java.nio.charset.CodingErrorAction

```
public final class CodingErrorAction
extends Object
```

A typesafe enumeration for coding-error actions.

Instances of this class are used to specify how malformed-input and unmappable-character errors are to be handled by charset decoders and encoders.

Since:

1.4

Field Summary

Fields

Modifier and Type	Field	Description
static final CodingErrorAction	**IGNORE**	Action indicating that a coding error is to be handled by dropping the erroneous input and resuming the coding operation.
static final CodingErrorAction	**REPLACE**	Action indicating that a coding error is to be handled by dropping the erroneous input, appending the coder's replacement value to the output buffer, and resuming the coding operation.
static final CodingErrorAction	**REPORT**	Action indicating that a coding error is to be reported, either by returning a CoderResult object or by throwing a CharacterCodingException, whichever is appropriate for the method

	implementing the coding process.

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
String	**toString**()	Returns a string describing this action.

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Field Details

IGNORE

```
public static final CodingErrorAction IGNORE
```

Action indicating that a coding error is to be handled by dropping the erroneous input and resuming the coding operation.

REPLACE

```
public static final CodingErrorAction REPLACE
```

Action indicating that a coding error is to be handled by dropping the erroneous input, appending the coder's replacement value to the output buffer, and resuming the coding operation.

REPORT

```
public static final CodingErrorAction REPORT
```

Action indicating that a coding error is to be reported, either by returning a `CoderResult` object or by throwing a `CharacterCodingException`, whichever is appropriate for the method implementing the coding process.

Method Details

toString

```
public String toString()
```

Returns a string describing this action.

Overrides:

`toString` in class `Object`

Returns:

A descriptive string

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.