JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class CharsetProvider

java.lang.Object
    java.nio.charset.spi.CharsetProvider

```
public abstract class CharsetProvider
extends Object
```

Charset service-provider class.

A charset provider is a concrete subclass of this class that has a zero-argument constructor and some number of associated `Charset` implementation classes. Charset providers are deployed on the application module path or the application class path. In order to be looked up, charset providers must be visible to the `system class loader`. See `Deploying Service Providers` for further
detail on deploying a charset provider as a module or on the class path.

For a charset provider deployed in a module, the *provides* directive must be specified in the module declaration. The provides directive specifies both the service and the service provider. In this case, the service is `java.nio.charset.spi.CharsetProvider`.

As an example, a charset provider deployed as a module might specify the following directive:

```
    provides java.nio.charset.spi.CharsetProvider with com.example.ExternalCharse
```

For a charset provider deployed on the class path, it identifies itself with a provider-configuration file named `java.nio.charset.spi.CharsetProvider` in the resource directory `META-INF/services`. The file should contain a list of fully-qualified concrete charset-provider class names, one per line. A line is terminated by any one of a line feed (`'\n'`), a carriage return (`'\r'`), or a carriage return followed immediately by a line feed. Space and tab characters surrounding each name, as well as blank lines, are ignored. The comment character is `'#'` (`'\u0023'`); on each line all characters following the first comment character are ignored. The file must be encoded in UTF-8.

If a particular concrete charset provider class is named in more than one configuration file, or is named in the same configuration file more than once, then the duplicates will be ignored. The configuration file naming a particular provider need not be in the same jar file or other distribution unit as the provider itself. The provider must be accessible from the same class loader that was initially queried to locate the configuration file; this is not necessarily the class loader that loaded the file.

Since:

1.4

See Also:

Charset

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**CharsetProvider**()	Initializes a new charset provider.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
abstract Charset	**charsetForName**(String charsetName)	Retrieves a charset for the given charset name.
abstract Iterator<Charset>	**charsets**()	Creates an iterator that iterates over the charsets supported by this provider.

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

CharsetProvider

```
protected CharsetProvider()
```

Initializes a new charset provider.

Method Details

charsets

```
public abstract Iterator<Charset> charsets()
```

Creates an iterator that iterates over the charsets supported by this provider. This method is used in the implementation of the `Charset.availableCharsets` method.

Returns:

The new iterator

charsetForName

```
public abstract Charset charsetForName(String charsetName)
```

Retrieves a charset for the given charset name.

Parameters:

`charsetName` - The name of the requested charset; may be either a canonical name or an alias

Returns:

A charset object for the named charset, or `null` if the named charset is not supported by this provider

---

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.