JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Enum Class AccessMode

java.lang.Object
    java.lang.Enum<AccessMode>
        java.nio.file.AccessMode

All Implemented Interfaces:

Serializable, Comparable<AccessMode>, Constable

```
public enum AccessMode
extends Enum<AccessMode>
```

Defines access modes used to test the accessibility of a file.

Since:

1.7

Nested Class Summary

Nested classes/interfaces declared in class Enum
Enum.EnumDesc<E>

Enum Constant Summary

Enum Constants

Enum Constant	Description
EXECUTE	Test execute access.
READ	Test read access.
WRITE	Test write access.

Method Summary

All Methods | **Static Methods**

Modifier and Type	Method	Description
static AccessMode	**valueOf**(String name)	Returns the enum constant of this class with the specified name.
static AccessMode[]	**values**()	Returns an array containing the constants

	of this enum class, in the order they are declared.

Methods declared in class Enum

`clone`, `compareTo`, `describeConstable`, `equals`, `finalize`, `getDeclaringClass`, `hashCode`, `name`, `ordinal`, `toString`, `valueOf`

Methods declared in class Object

`getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Enum Constant Details

READ

```
public static final AccessMode READ
```

Test read access.

WRITE

```
public static final AccessMode WRITE
```

Test write access.

EXECUTE

```
public static final AccessMode EXECUTE
```

Test execute access.

Method Details

values

```
public static AccessMode[] values()
```

Returns an array containing the constants of this enum class, in the order they are declared.

Returns:

an array containing the constants of this enum class, in the order they are declared

valueOf

```
public static AccessMode valueOf(String name)
```

Returns the enum constant of this class with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this class. (Extraneous whitespace characters are not permitted.)

Parameters:

`name` - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

`IllegalArgumentException` - if this enum class has no constant with the specified name

`NullPointerException` - if the argument is null

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.