JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface WatchEvent<T>

Type Parameters:

T - The type of the context object associated with the event

`public interface WatchEvent<T>`

An event or a repeated event for an object that is registered with a `WatchService`.

An event is classified by its `kind` and has a `count` to indicate the number of times that the event has been observed. This allows for efficient representation of repeated events. The `context` method returns any context associated with the event. In the case of a repeated event then the context is the same for all events.

Watch events are immutable and safe for use by multiple concurrent threads.

Since:

1.7

Nested Class Summary

Nested Classes

Modifier and Type	Interface	Description
`static interface`	`WatchEvent.Kind<T>`	An event kind, for the purposes of identification.
`static interface`	`WatchEvent.Modifier`	An event modifier that qualifies how a `Watchable` is registered with a `WatchService`.

Method Summary

All Methods | **Instance Methods** |

Modifier and Type	Method	Description
`T`	`context()`	Returns the context for the event.
`int`	`count()`	Returns the event count.

`WatchEvent.Kind<T>` **`kind`**`()`	Returns the event kind.

Method Details

kind

`WatchEvent.Kind<T> kind()`

Returns the event kind.

Returns:

the event kind

count

`int count()`

Returns the event count. If the event count is greater than 1 then this is a repeated event.

Returns:

the event count

context

`T context()`

Returns the context for the event.

In the case of `ENTRY_CREATE`, `ENTRY_DELETE`, and `ENTRY_MODIFY` events the context is a `Path` that is the `relative` path between the directory registered with the watch service, and the entry that is created, deleted, or modified.

Returns:

the event context; may be `null`

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.