JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class AclEntry

java.lang.Object
    java.nio.file.attribute.AclEntry

```
public final class AclEntry
extends Object
```

An entry in an access control list (ACL).

The
ACL entry represented by this class is based on the ACL model specified in *RFC 3530: Network File System (NFS) version 4 Protocol*. Each entry has four components as follows:

1. The `type` component determines if the entry grants or denies access.
2. The `principal` component, sometimes called the "who" component, is a `UserPrincipal` corresponding to the identity that the entry grants or denies access
3. The `permissions` component is a set of `permissions`
4. The `flags` component is a set of `flags` to indicate how entries are inherited and propagated

ACL entries are created using an associated `AclEntry.Builder` object by invoking its `build` method.

ACL entries are immutable and are safe for use by multiple concurrent threads.

Since:

1.7

External Specifications

RFC 3530: Network File System (NFS) version 4 Protocol

Nested Class Summary

Nested Classes

Modifier and Type	Class	Description
`static final class`	**`AclEntry.Builder`**	A builder of `AclEntry` objects.

Method Summary

All Methods	Static Methods	

Modifier and Type	Method	Description
boolean	**equals**(Object ob)	Compares the specified object with this ACL entry for equality.
Set<AclEntryFlag>	**flags**()	Returns a copy of the flags component.
int	**hashCode**()	Returns the hash-code value for this ACL entry.
static AclEntry.Builder	**newBuilder**()	Constructs a new builder.
static AclEntry.Builder	**newBuilder**(AclEntry entry)	Constructs a new builder with the components of an existing ACL entry.
Set<AclEntryPermission>	**permissions**()	Returns a copy of the permissions component.
UserPrincipal	**principal**()	Returns the principal component.
String	**toString**()	Returns the string representation of this ACL entry.
AclEntryType	**type**()	Returns the ACL entry type.

Methods declared in class Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Method Details

newBuilder

```
public static AclEntry.Builder newBuilder()
```

Constructs a new builder. The initial value of the type and who components is `null`. The initial value of the permissions and flags components is the empty set.

Returns:

a new builder

newBuilder

```
public static AclEntry.Builder newBuilder(AclEntry entry)
```

Constructs a new builder with the components of an existing ACL entry.

Parameters:

`entry` - an ACL entry

Returns:

a new builder

type

```
public AclEntryType type()
```

Returns the ACL entry type.

Returns:

the ACL entry type

principal

```
public UserPrincipal principal()
```

Returns the principal component.

Returns:

the principal component

permissions

```
public Set<AclEntryPermission> permissions()
```

Returns a copy of the permissions component.

The returned set is a modifiable copy of the permissions.

Returns:

the permissions component

flags

```
public Set<AclEntryFlag> flags()
```

Returns a copy of the flags component.

The returned set is a modifiable copy of the flags.

Returns:

the flags component

equals

```
public boolean equals(Object ob)
```

Compares the specified object with this ACL entry for equality.

If the given object is not an `AclEntry` then this method immediately returns `false`.

For two ACL entries to be considered equals requires that they are both the same type, their who components are equal, their permissions components are equal, and their flags components are equal.

This method satisfies the general contract of the `Object.equals` method.

Overrides:

`equals` in class `Object`

Parameters:

`ob` - the object to which this object is to be compared

Returns:

`true` if, and only if, the given object is an AclEntry that is identical to this AclEntry

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public int hashCode()
```

Returns the hash-code value for this ACL entry.

This method satisfies the general contract of the `Object.hashCode()` method.

Overrides:

`hashCode` in class `Object`

Returns:

a hash code value for this object

See Also:

`Object.equals(java.lang.Object)`,
`System.identityHashCode(Object)`

toString

```
public String toString()
```

Returns the string representation of this ACL entry.

Overrides:

`toString` in class `Object`

Returns:

the string representation of this entry

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.