JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface DosFileAttributeView

All Superinterfaces:

AttributeView, BasicFileAttributeView, FileAttributeView

```
public interface DosFileAttributeView
extends BasicFileAttributeView
```

A file attribute view that provides a view of the legacy "DOS" file attributes. These attributes are supported by file systems such as the File Allocation Table (FAT) format commonly used in *consumer devices*.

A `DosFileAttributeView` is a `BasicFileAttributeView` that additionally supports access to the set of DOS attribute flags that are used to indicate if the file is read-only, hidden, a system file, or archived.

Where dynamic access to file attributes is required, the attributes supported by this attribute view are as defined by `BasicFileAttributeView`, and in addition, the following attributes are supported:

Name	Type
readonly	Boolean
hidden	Boolean
system	Boolean
archive	Boolean

The `getAttribute` method may be used to read any of these attributes, or any of the attributes defined by `BasicFileAttributeView` as if by invoking the `readAttributes()` method.

The `setAttribute` method may be used to update the file's last modified time, last access time or create time attributes as defined by `BasicFileAttributeView`. It may also be used to update the DOS attributes as if by invoking the `setReadOnly`, `setHidden`, `setSystem`, and `setArchive` methods respectively.

Since:

1.7

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
String	**name**()	

		Returns the name of the attribute view.
DosFileAttributes	**readAttributes**()	Reads the basic file attributes as a bulk operation.
void	**setArchive**(boolean value)	Updates the value of the archive attribute.
void	**setHidden**(boolean value)	Updates the value of the hidden attribute.
void	**setReadOnly**(boolean value)	Updates the value of the read-only attribute.
void	**setSystem**(boolean value)	Updates the value of the system attribute.

Methods declared in interface BasicFileAttributeView

setTimes

Method Details

name

String name()

Returns the name of the attribute view. Attribute views of this type have the name "dos".

Specified by:

name in interface AttributeView

Specified by:

name in interface BasicFileAttributeView

Returns:

the name of the attribute view

readAttributes

DosFileAttributes readAttributes()
throws IOException

Description copied from interface: BasicFileAttributeView

Reads the basic file attributes as a bulk operation.

It is implementation specific if all file attributes are read as an atomic operation with respect to other file system operations.

Specified by:

`readAttributes` in interface `BasicFileAttributeView`

Returns:

the file attributes

Throws:

`IOException` - if an I/O error occurs

setReadOnly

```
void setReadOnly(boolean value)
          throws IOException
```

Updates the value of the read-only attribute.

It is implementation specific if the attribute can be updated as an atomic operation with respect to other file system operations. An implementation may, for example, require to read the existing value of the DOS attribute in order to update this attribute.

Parameters:

`value` - the new value of the attribute

Throws:

`IOException` - if an I/O error occurs

setHidden

```
void setHidden(boolean value)
        throws IOException
```

Updates the value of the hidden attribute.

It is implementation specific if the attribute can be updated as an atomic operation with respect to other file system operations. An implementation may, for example, require to read the existing value of the DOS attribute in order to update this attribute.

Parameters:

`value` - the new value of the attribute

Throws:

`IOException` - if an I/O error occurs

setSystem

```
void setSystem(boolean value)
        throws IOException
```

Updates the value of the system attribute.

It is implementation specific if the attribute can be updated as an atomic operation with respect to other file system operations. An implementation may, for example, require to read the existing value of the DOS attribute in order to update this attribute.

Parameters:

`value` - the new value of the attribute

Throws:

`IOException` - if an I/O error occurs

setArchive

```
void setArchive(boolean value)
         throws IOException
```

Updates the value of the archive attribute.

It is implementation specific if the attribute can be updated as an atomic operation with respect to other file system operations. An implementation may, for example, require to read the existing value of the DOS attribute in order to update this attribute.

Parameters:

`value` - the new value of the attribute

Throws:

`IOException` - if an I/O error occurs

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.