JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface DosFileAttributes

All Superinterfaces:

BasicFileAttributes

```
public interface DosFileAttributes
extends BasicFileAttributes
```

File attributes associated with a file in a file system that supports legacy "DOS" attributes.

Usage Example:

```
    Path file = ...
    DosFileAttributes attrs = Files.readAttributes(file, DosFileAttributes.class);
```

Since:

1.7

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
boolean	isArchive()	Returns the value of the archive attribute.
boolean	isHidden()	Returns the value of the hidden attribute.
boolean	isReadOnly()	Returns the value of the read-only attribute.
boolean	isSystem()	Returns the value of the system attribute.

Methods declared in interface BasicFileAttributes

`creationTime`, `fileKey`, `isDirectory`, `isOther`, `isRegularFile`, `isSymbolicLink`, `lastAccessTime`, `lastModifiedTime`, `size`

Method Details

isReadOnly

`boolean isReadOnly()`

Returns the value of the read-only attribute.

This attribute is often used as a simple access control mechanism to prevent files from being deleted or updated. Whether the file system or platform does any enforcement to prevent *read-only* files from being updated is implementation specific.

Returns:

the value of the read-only attribute

isHidden

`boolean isHidden()`

Returns the value of the hidden attribute.

This attribute is often used to indicate if the file is visible to users.

Returns:

the value of the hidden attribute

isArchive

`boolean isArchive()`

Returns the value of the archive attribute.

This attribute is typically used by backup programs.

Returns:

the value of the archive attribute

isSystem

`boolean isSystem()`

Returns the value of the system attribute.

This attribute is often used to indicate that the file is a component of the operating system.

Returns:

the value of the system attribute

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.