JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface FileAttribute<T>

Type Parameters:

T - The type of the file attribute value

`public interface FileAttribute<T>`

An object that encapsulates the value of a file attribute that can be set atomically when creating a new file or directory by invoking the `createFile` or `createDirectory` methods.

Since:

1.7

See Also:

`PosixFilePermissions.asFileAttribute(Set)`

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
`String`	**`name`**`()`	Returns the attribute name.
`T`	**`value`**`()`	Returns the attribute value.

Method Details

name

`String name()`

Returns the attribute name.

Returns:

The attribute name

value

`T value()`

Returns the attribute value.

Returns:

The attribute value

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.