JavaScript is disabled on your browser.

Interface GroupPrincipal

All Superinterfaces:

Principal, UserPrincipal

```
public interface GroupPrincipal
extends UserPrincipal
```

A `UserPrincipal` representing a *group identity*, used to determine access rights to objects in a file system. The exact definition of a group is implementation specific, but typically, it represents an identity created for administrative purposes so as to determine the access rights for the members of the group. Whether an entity can be a member of multiple groups, and whether groups can be nested, are implementation specified and therefore not specified.

Since:

1.7

See Also:

UserPrincipalLookupService.lookupPrincipalByGroupName(String)

Method Summary

Methods declared in interface Principal

equals, getName, hashCode, implies, toString

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.