JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class PosixFilePermissions

java.lang.Object
    java.nio.file.attribute.PosixFilePermissions

```
public final class PosixFilePermissions
extends Object
```

This class consists exclusively of static methods that operate on sets of `PosixFilePermission` objects.

Since:

1.7

Method Summary

All Methods	Static Methods	

Modifier and Type	Method	Description
static `FileAttribute<Set<PosixFilePermis`	**asFileAttribute** (`Set<PosixFilePermission`	Creates a `FileAttribute`, encapsulating a copy of the given file permissions, suitable for passing to the `createFile` or `createDirectory` methods.
static `Set<PosixFilePermission:`	**fromString** (`String` perms)	Returns the set of permissions corresponding to a given `String` representation.
static `String`	**toString** (`Set<PosixFilePermission`	Returns the `String` representation of a set of permissions.

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Method Details

toString

```
public static String toString(Set<PosixFilePermission> perms)
```

Returns the `String` representation of a set of permissions. It is guaranteed that the returned `String` can be parsed by the `fromString(String)` method.

If the set contains `null` or elements that are not of type `PosixFilePermission` then these elements are ignored.

Parameters:

`perms` - the set of permissions

Returns:

the string representation of the permission set

fromString

```
public static Set<PosixFilePermission> fromString(String perms)
```

Returns the set of permissions corresponding to a given `String` representation.

The `perms` parameter is a `String` representing the permissions. It has 9 characters that are interpreted as three sets of three. The first set refers to the owner's permissions; the next to the group permissions and the last to others. Within each set, the first character is `'r'` to indicate permission to read, the second character is `'w'` to indicate permission to write, and the third character is `'x'` for execute permission. Where a permission is not set then the corresponding character is set to `'-'`.

Usage Example: Suppose we require the set of permissions that indicate the owner has read, write, and execute permissions, the group has read and execute permissions and others have none.

```
    Set<PosixFilePermission> perms = PosixFilePermissions.fromString("rwxr-x---"
```

Parameters:

`perms` - string representing a set of permissions

Returns:

the resulting set of permissions

Throws:

`IllegalArgumentException` - if the string cannot be converted to a set of permissions

See Also:

`toString(Set)`

asFileAttribute

```
public static FileAttribute<Set<PosixFilePermission>> asFileAttribute
(Set<PosixFilePermission> perms)
```

Creates a `FileAttribute`, encapsulating a copy of the given file permissions, suitable for passing to the `createFile` or `createDirectory` methods.

Parameters:

`perms` - the set of permissions

Returns:

an attribute encapsulating the given file permissions with `name` `"posix:permissions"`

Throws:

`ClassCastException` - if the set contains elements that are not of type `PosixFilePermission`

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.