JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class UserPrincipalLookupService

java.lang.Object
    java.nio.file.attribute.UserPrincipalLookupService

```
public abstract class UserPrincipalLookupService
extends Object
```

An object to lookup user and group principals by name. A `UserPrincipal` represents an identity that may be used to determine access rights to objects in a file system. A `GroupPrincipal` represents a *group identity*. A `UserPrincipalLookupService` defines methods to lookup identities by name or group name (which are typically user or account names). Whether names and group names are case sensitive or not depends on the implementation. The exact definition of a group is implementation specific but typically a group represents an identity created for administrative purposes so as to determine the access rights for the members of the group. In particular it is implementation specific if the *namespace* for names and groups is the same or is distinct. To ensure consistent and correct behavior across platforms it is recommended that this API be used as if the namespaces are distinct. In other words, the `lookupPrincipalByName` should be used to lookup users, and `lookupPrincipalByGroupName` should be used to lookup groups.

Since:

1.7

See Also:

`FileSystem.getUserPrincipalLookupService()`

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**UserPrincipalLookupServi**	Initializes a new instance of this class.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
abstract GroupPrincipal	**lookupPrincipalByGroupNa**(String group)	Lookup a group principal by group name.

abstract UserPrincipal	**lookupPrincipalByName** (String name)	Lookup a user principal by name.

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

UserPrincipalLookupService

```
protected UserPrincipalLookupService()
```

Initializes a new instance of this class.

Method Details

lookupPrincipalByName

```
public abstract UserPrincipal lookupPrincipalByName(String name)
                                             throws IOException
```

Lookup a user principal by name.

Parameters:

name - the string representation of the user principal to lookup

Returns:

a user principal

Throws:

UserPrincipalNotFoundException - the principal does not exist

IOException - if an I/O error occurs

lookupPrincipalByGroupName

```
public abstract GroupPrincipal lookupPrincipalByGroupName
(String group)
                                                  throws IOException
```

Lookup a group principal by group name.

Where an implementation does not support any notion of group then this method always throws UserPrincipalNotFoundException. Where the namespace for user accounts and groups is the same, then this method is identical to invoking lookupPrincipalByName.

Parameters:

`group` - the string representation of the group to lookup

Returns:

a group principal

Throws:

`UserPrincipalNotFoundException` - the principal does not exist or is not a group

`IOException` - if an I/O error occurs

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.