JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class AttributedCharacterIterator.Attribute

java.lang.Object
  java.text.AttributedCharacterIterator.Attribute

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

Format.Field, TextAttribute

Enclosing interface:

AttributedCharacterIterator

```
public static class AttributedCharacterIterator.Attribute
extends Object
implements Serializable
```

Defines attribute keys that are used to identify text attributes. These keys are used in `AttributedCharacterIterator` and `AttributedString`.

Since:

1.2

See Also:

AttributedCharacterIterator, AttributedString, Serialized Form

Field Summary

Fields

Modifier and Type	Field	Description
static final AttributedCharacterI	INPUT_METHOD_SEGMENT	Attribute key for input method segments.
static final AttributedCharacterI	LANGUAGE	Attribute key for the language of some text.
static final AttributedCharacterI	READING	Attribute key for the reading of some text.

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	Attribute(String name)	

	Constructs an `Attribute` with the given name.

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
`final boolean`	**`equals`**`(Object obj)`	Compares two objects for equality.
`protected String`	**`getName`**`()`	Returns the name of the attribute.
`final int`	**`hashCode`**`()`	Returns a hash code value for the object.
`protected Object`	**`readResolve`**`()`	Resolves instances being deserialized to the predefined constants.
`String`	**`toString`**`()`	Returns a string representation of the object.

Methods declared in class Object

`clone`, `finalize`, `getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Field Details

LANGUAGE

`public static final AttributedCharacterIterator.Attribute LANGUAGE`

Attribute key for the language of some text.

Values are instances of `Locale`.

See Also:

`Locale`

READING

`public static final AttributedCharacterIterator.Attribute READING`

Attribute key for the reading of some text. In languages where the written form and the pronunciation of a word are only loosely related (such as Japanese), it is often necessary to store the reading (pronunciation) along with the written form.

Values are instances of `Annotation` holding instances of `String`.

See Also:

`Annotation`, `String`

INPUT_METHOD_SEGMENT

```
public static
final AttributedCharacterIterator.Attribute INPUT_METHOD_SEGMENT
```

Attribute key for input method segments. Input methods often break up text into segments, which usually correspond to words.

Values are instances of `Annotation` holding a `null` reference.

See Also:

`Annotation`

Constructor Details

Attribute

```
protected Attribute(String name)
```

Constructs an `Attribute` with the given name.

Parameters:

`name` - the name of `Attribute`

Method Details

equals

```
public final boolean equals(Object obj)
```

Compares two objects for equality. This version only returns true for `x.equals(y)` if `x` and `y` refer to the same object, and guarantees this for all subclasses.

Overrides:

`equals` in class `Object`

Parameters:

`obj` - the reference object with which to compare.

Returns:

`true` if this object is the same as the obj argument; `false` otherwise.

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public final int hashCode()
```

Returns
a hash code value for the object. This version is identical to the one in `Object`, but is also final.

Overrides:

`hashCode` in class `Object`

Returns:

a hash code value for this object

See Also:

`Object.equals(java.lang.Object)`,
`System.identityHashCode(Object)`

toString

```
public String toString()
```

Returns a string representation of the object. This version returns the concatenation of class name, `"("`, a name identifying the attribute and `")"`.

Overrides:

`toString` in class `Object`

Returns:

a string representation of the object

getName

```
protected String getName()
```

Returns the name of the attribute.

Returns:

the name of `Attribute`

readResolve

```
protected Object readResolve()
                     throws InvalidObjectException
```

Resolves instances being deserialized to the predefined constants.

Returns:

the resolved `Attribute` object

Throws:

`InvalidObjectException` - if the object to resolve is not an instance of `Attribute`

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.