JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class AttributedString

java.lang.Object
    java.text.AttributedString

```
public class AttributedString
extends Object
```

An AttributedString holds text and related attribute information. It may be used as the actual data storage in some cases where a text reader wants to access attributed text through the AttributedCharacterIterator interface.

An attribute is a key/value pair, identified by the key. No two attributes on a given character can have the same key.

The values for an attribute are immutable, or must not be mutated by clients or storage. They are always passed by reference, and not cloned.

Since:

1.2

See Also:

AttributedCharacterIterator, Annotation

Constructor Summary

Constructors

Constructor	Description
AttributedString(String text)	Constructs an AttributedString instance with the given text.
AttributedString(String text, Map<? extends AttributedCharacterIterator.Attribu > attributes)	Constructs an AttributedString instance with the given text and attributes.
AttributedString (AttributedCharacterIterator text)	Constructs an AttributedString instance with the given attributed text represented by AttributedCharacterIterator.
AttributedString (AttributedCharacterIterator text, int beginIndex, int endIndex)	Constructs an AttributedString instance with the subrange of the given attributed text represented by AttributedCharacterIterator.

AttributedString(AttributedCharacterIterator text, int beginIndex, int endIndex, AttributedCharacterIterator.Attribu	Constructs an AttributedString instance with the subrange of the given attributed text represented by AttributedCharacterIterator.

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
void	**addAttribute**(AttributedCharacterIter Object value)	Adds an attribute to the entire string.
void	**addAttribute**(AttributedCharacterIter Object value, int beginIndex, int endIndex)	Adds an attribute to a subrange of the string.
void	**addAttributes**(Map<? extends AttributedCharacterItera > attributes, int beginIndex, int endIndex)	Adds a set of attributes to a subrange of the string.
AttributedCharacterI	**getIterator**()	Creates an AttributedCharacterIterator instance that provides access to the entire contents of this string.
AttributedCharacterI	**getIterator**(AttributedCharacterIter	Creates an AttributedCharacterIterator instance that provides access to selected contents of this string.
AttributedCharacterI	**getIterator**(AttributedCharacterIter int beginIndex, int endIndex)	Creates an AttributedCharacterIterator instance that provides access to selected contents of this string.

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

AttributedString

```
public AttributedString(String text)
```

Constructs an AttributedString instance with the given text.

Parameters:

`text` - The text for this attributed string.

Throws:

`NullPointerException` - if `text` is null.

AttributedString

```
public AttributedString
(String text,
 Map<? extends AttributedCharacterIterator.Attribute, ?> attributes)
```

Constructs an AttributedString instance with the given text and attributes.

Parameters:

`text` - The text for this attributed string.

`attributes` - The attributes that apply to the entire string.

Throws:

`NullPointerException` - if `text` or `attributes` is null.

`IllegalArgumentException` - if the text has length 0 and the attributes parameter is not an empty Map (attributes cannot be applied to a 0-length range).

AttributedString

```
public AttributedString(AttributedCharacterIterator text)
```

Constructs an AttributedString instance with the given attributed text represented by AttributedCharacterIterator.

Parameters:

`text` - The text for this attributed string.

Throws:

NullPointerException - if text is null.

AttributedString

```
public AttributedString(AttributedCharacterIterator text,
                        int beginIndex,
                        int endIndex)
```

Constructs an AttributedString instance with the subrange of the given attributed text represented by AttributedCharacterIterator. If the given range produces an empty text, all attributes will be discarded. Note that any attributes wrapped by an Annotation object are discarded for a subrange of the original attribute range.

Parameters:

text - The text for this attributed string.

beginIndex - Index of the first character of the range.

endIndex - Index of the character following the last character of the range.

Throws:

NullPointerException - if text is null.

IllegalArgumentException - if the subrange given by beginIndex and endIndex is out of the text range.

See Also:

Annotation

AttributedString

```
public AttributedString
(AttributedCharacterIterator text,
 int beginIndex,
 int endIndex,
 AttributedCharacterIterator.Attribute[] attributes)
```

Constructs an AttributedString instance with the subrange of the given attributed text represented by AttributedCharacterIterator. Only attributes that match the given attributes will be incorporated into the instance. If the given range produces an empty text, all attributes will be discarded. Note that any attributes wrapped by an Annotation object are discarded for a subrange of the original attribute range.

Parameters:

text - The text for this attributed string.

beginIndex - Index of the first character of the range.

endIndex - Index of the character following the last character of the range.

`attributes` - Specifies attributes to be extracted from the text. If null is specified, all available attributes will be used.

Throws:

`NullPointerException` - if `text` is null.

`IllegalArgumentException` - if the subrange given by beginIndex and endIndex is out of the text range.

See Also:

`Annotation`

Method Details

addAttribute

```
public void addAttribute
(AttributedCharacterIterator.Attribute attribute,
 Object value)
```

Adds an attribute to the entire string.

Parameters:

`attribute` - the attribute key

`value` - the value of the attribute; may be null

Throws:

`NullPointerException` - if `attribute` is null.

`IllegalArgumentException` - if the AttributedString has length 0 (attributes cannot be applied to a 0-length range).

addAttribute

```
public void addAttribute
(AttributedCharacterIterator.Attribute attribute,
 Object value,
 int beginIndex,
 int endIndex)
```

Adds an attribute to a subrange of the string.

Parameters:

`attribute` - the attribute key

`value` - The value of the attribute. May be null.

`beginIndex` - Index of the first character of the range.

`endIndex` - Index of the character following the last character of the range.

Throws:

`NullPointerException` - if `attribute` is null.

`IllegalArgumentException` - if beginIndex is less than 0, endIndex is greater than the length of the string, or beginIndex and endIndex together don't define a non-empty subrange of the string.

addAttributes

```
public void addAttributes
(Map<? extends AttributedCharacterIterator.Attribute, ?> attributes,
 int beginIndex,
 int endIndex)
```

Adds a set of attributes to a subrange of the string.

Parameters:

`attributes` - The attributes to be added to the string.

`beginIndex` - Index of the first character of the range.

`endIndex` - Index of the character following the last character of the range.

Throws:

`NullPointerException` - if `attributes` is null.

`IllegalArgumentException` - if beginIndex is less than 0, endIndex is greater than the length of the string, or beginIndex and endIndex together don't define a non-empty subrange of the string and the attributes parameter is not an empty Map.

getIterator

```
public AttributedCharacterIterator getIterator()
```

Creates an AttributedCharacterIterator instance that provides access to the entire contents of this string.

Returns:

An iterator providing access to the text and its attributes.

getIterator

```
public AttributedCharacterIterator getIterator
(AttributedCharacterIterator.Attribute[] attributes)
```

Creates an AttributedCharacterIterator instance that provides access to selected contents of this string. Information about attributes not listed in attributes that the implementor may have need not be made accessible

through the iterator. If the list is null, all available attribute information should be made accessible.

Parameters:

`attributes` - a list of attributes that the client is interested in

Returns:

an iterator providing access to the entire text and its selected attributes

getIterator

```
public AttributedCharacterIterator getIterator
(AttributedCharacterIterator.Attribute[] attributes,
 int beginIndex,
 int endIndex)
```

Creates an AttributedCharacterIterator instance that provides access to selected contents of this string. Information about attributes not listed in attributes that the implementor may have need not be made accessible through the iterator. If the list is null, all available attribute information should be made accessible.

Parameters:

`attributes` - a list of attributes that the client is interested in

`beginIndex` - the index of the first character

`endIndex` - the index of the character following the last character

Returns:

an iterator providing access to the text and its attributes

Throws:

`IllegalArgumentException` - if beginIndex is less than 0, endIndex is greater than the length of the string, or beginIndex is greater than endIndex.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.