JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class DateFormat.Field

java.lang.Object
  java.text.AttributedCharacterIterator.Attribute
    java.text.Format.Field
      java.text.DateFormat.Field

All Implemented Interfaces:

Serializable

Enclosing class:

DateFormat

```
public static class DateFormat.Field
extends Format.Field
```

Defines constants that are used as attribute keys in the `AttributedCharacterIterator` returned from `DateFormat.formatToCharacterIterator` and as field identifiers in `FieldPosition`.

The class also provides two methods to map between its constants and the corresponding Calendar constants.

Since:

1.4

See Also:

Calendar, Serialized Form

Field Summary

Fields

Modifier and Type	Field	Description
static final DateFormat.Field	AM_PM	Constant identifying the time of day indicator (e.g. "a.m." or "p.m.") field.
static final DateFormat.Field	DAY_OF_MONTH	Constant identifying the day of month field.
static final DateFormat.Field	DAY_OF_WEEK	Constant identifying the day of week field.
static final DateFormat.Field	DAY_OF_WEEK_IN_MONTH	Constant identifying the day of week field.

static final DateFormat.Field	**DAY_OF_YEAR**	Constant identifying the day of year field.
static final DateFormat.Field	**ERA**	Constant identifying the era field.
static final DateFormat.Field	**HOUR_OF_DAY0**	Constant identifying the hour of day field, where the legal values are 0 to 23.
static final DateFormat.Field	**HOUR_OF_DAY1**	Constant identifying the hour of day field, where the legal values are 1 to 24.
static final DateFormat.Field	**HOUR0**	Constant identifying the hour field, where the legal values are 0 to 11.
static final DateFormat.Field	**HOUR1**	Constant identifying the hour field, where the legal values are 1 to 12.
static final DateFormat.Field	**MILLISECOND**	Constant identifying the millisecond field.
static final DateFormat.Field	**MINUTE**	Constant identifying the minute field.
static final DateFormat.Field	**MONTH**	Constant identifying the month field.
static final DateFormat.Field	**SECOND**	Constant identifying the second field.
static final DateFormat.Field	**TIME_ZONE**	Constant identifying the time zone field.
static final DateFormat.Field	**WEEK_OF_MONTH**	Constant identifying the week of month field.
static final DateFormat.Field	**WEEK_OF_YEAR**	Constant identifying the week of year field.
static final DateFormat.Field	**YEAR**	Constant identifying the year field.

Fields declared in class AttributedCharacterIterator.Attribute

INPUT_METHOD_SEGMENT, LANGUAGE, READING

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**Field**(String name, int calendarField)	Creates a Field.

Method Summary

All Methods | **Static Methods**

Modifier and Type	Method	Description
int	**getCalendarField**()	Returns the Calendar field associated with this attribute.
static DateFormat.Field	**ofCalendarField** (int calendarField)	Returns the Field constant that corresponds to the Calendar constant calendarField.
protected Object	**readResolve**()	Resolves instances being deserialized to the predefined constants.

Methods declared in class AttributedCharacterIterator.Attribute

equals, getName, hashCode, toString

Methods declared in class Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Field Details

ERA

public static final DateFormat.Field ERA

Constant identifying the era field.

YEAR

public static final DateFormat.Field YEAR

Constant identifying the year field.

MONTH

public static final DateFormat.Field MONTH

Constant identifying the month field.

DAY_OF_MONTH

public static final DateFormat.Field DAY_OF_MONTH

Constant identifying the day of month field.

HOUR_OF_DAY1

public static final DateFormat.Field HOUR_OF_DAY1

Constant identifying the hour of day field, where the legal values are 1 to 24.

HOUR_OF_DAY0

public static final DateFormat.Field HOUR_OF_DAY0

Constant identifying the hour of day field, where the legal values are 0 to 23.

MINUTE

public static final DateFormat.Field MINUTE

Constant identifying the minute field.

SECOND

`public static final DateFormat.Field SECOND`

Constant identifying the second field.

MILLISECOND

`public static final DateFormat.Field MILLISECOND`

Constant identifying the millisecond field.

DAY_OF_WEEK

`public static final DateFormat.Field DAY_OF_WEEK`

Constant identifying the day of week field.

DAY_OF_YEAR

`public static final DateFormat.Field DAY_OF_YEAR`

Constant identifying the day of year field.

DAY_OF_WEEK_IN_MONTH

`public static final DateFormat.Field DAY_OF_WEEK_IN_MONTH`

Constant identifying the day of week field.

WEEK_OF_YEAR

`public static final DateFormat.Field WEEK_OF_YEAR`

Constant identifying the week of year field.

WEEK_OF_MONTH

`public static final DateFormat.Field WEEK_OF_MONTH`

Constant identifying the week of month field.

AM_PM

`public static final DateFormat.Field AM_PM`

Constant identifying the time of day indicator (e.g. "a.m." or "p.m.") field.

HOUR1

```
public static final DateFormat.Field HOUR1
```

Constant identifying the hour field, where the legal values are 1 to 12.

HOUR0

```
public static final DateFormat.Field HOUR0
```

Constant identifying the hour field, where the legal values are 0 to 11.

TIME_ZONE

```
public static final DateFormat.Field TIME_ZONE
```

Constant identifying the time zone field.

Constructor Details

Field

```
protected Field(String name,
                int calendarField)
```

Creates a `Field`.

Parameters:

`name` - the name of the `Field`

`calendarField` - the `Calendar` constant this `Field` corresponds to; any value, even one outside the range of legal `Calendar` values may be used, but `-1` should be used for values that don't correspond to legal `Calendar` values

Method Details

ofCalendarField

```
public static DateFormat.Field ofCalendarField(int calendarField)
```

Returns the `Field` constant that corresponds to the `Calendar` constant `calendarField`. If there is no direct mapping between the `Calendar` constant and a `Field`, null is returned.

Parameters:

`calendarField` - Calendar field constant

Returns:

Field instance representing calendarField.

Throws:

`IllegalArgumentException` - if `calendarField` is not the value of a `Calendar` field constant.

See Also:

`Calendar`

getCalendarField

```
public int getCalendarField()
```

Returns the `Calendar` field associated with this attribute. For example, if this represents the hours field of a `Calendar`, this method would return `Calendar.HOUR`. The return value of `-1` guarantees that this field does not represent any corresponding constant in `Calendar`.

Implementation Requirements:

The default implementation always returns `-1` if it does not represent any corresponding constant in `Calendar`.

Returns:

Calendar constant for this field

See Also:

`Calendar`

readResolve

```
protected Object readResolve()
                     throws InvalidObjectException
```

Resolves instances being deserialized to the predefined constants.

Overrides:

`readResolve` in class `AttributedCharacterIterator.Attribute`

Returns:

resolved DateFormat.Field constant

Throws:

`InvalidObjectException` - if the constant could not be resolved.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA

94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.