JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class FieldPosition

java.lang.Object
    java.text.FieldPosition

```
public class FieldPosition
extends Object
```

`FieldPosition` is a simple class used by `Format` and its subclasses to identify fields in formatted output. Fields can be identified in two ways:

- By an integer constant, whose names typically end with `_FIELD`. The constants are defined in the various subclasses of `Format`.
- By a `Format.Field` constant, see `ERA_FIELD` and its friends in `DateFormat` for an example.

`FieldPosition` keeps track of the position of the field within the formatted output with two indices: the index of the first character of the field and the index of the last character of the field.

One version of the `format` method in the various `Format` classes requires a `FieldPosition` object as an argument. You use this `format` method to perform partial formatting or to get information about the formatted output (such as the position of a field).

If you are interested in the positions of all attributes in the formatted string use the `Format` method `formatToCharacterIterator`.

Since:

1.1

See Also:

`Format`

Constructor Summary

Constructors

Constructor	Description
FieldPosition(int field)	Creates a FieldPosition object for the given field.
FieldPosition (Format.Field attribute)	Creates a FieldPosition object for the given field constant.
FieldPosition (Format.Field attribute, int fieldID)	Creates a `FieldPosition` object for the given field.

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
boolean	**equals**(Object obj)	Overrides equals
int	**getBeginIndex**()	Retrieves the index of the first character in the requested field.
int	**getEndIndex**()	Retrieves the index of the character following the last character in the requested field.
int	**getField**()	Retrieves the field identifier.
Format.Field	**getFieldAttribute**()	Returns the field identifier as an attribute constant from one of the `Field` subclasses.
int	**hashCode**()	Returns a hash code for this FieldPosition.
void	**setBeginIndex**(int bi)	Sets the begin index.
void	**setEndIndex**(int ei)	Sets the end index.
String	**toString**()	Return a string representation of this FieldPosition.

Methods declared in class Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Constructor Details

FieldPosition

```
public FieldPosition(int field)
```

Creates a FieldPosition object for the given field. Fields are identified by constants, whose names typically end with _FIELD, in the various subclasses of Format.

Parameters:

`field` - the field identifier

See Also:

`NumberFormat.INTEGER_FIELD`, `NumberFormat.FRACTION_FIELD`, `DateFormat.YEAR_FIELD`, `DateFormat.MONTH_FIELD`

FieldPosition

```
public FieldPosition(Format.Field attribute)
```

Creates a FieldPosition object for the given field constant. Fields are identified by constants defined in the various `Format` subclasses. This is equivalent to calling `new FieldPosition(attribute, -1)`.

Parameters:

`attribute` - Format.Field constant identifying a field

Since:

1.4

FieldPosition

```
public FieldPosition(Format.Field attribute,
                     int fieldID)
```

Creates a `FieldPosition` object for the given field. The field is identified by an attribute constant from one of the `Field` subclasses as well as an integer field ID defined by the `Format` subclasses. `Format` subclasses that are aware of `Field` should give precedence to `attribute` and ignore `fieldID` if `attribute` is not null. However, older `Format` subclasses may not be aware of `Field` and rely on `fieldID`. If the field has no corresponding integer constant, `fieldID` should be -1.

Parameters:

`attribute` - Format.Field constant identifying a field

`fieldID` - integer constant identifying a field

Since:

1.4

Method Details

getFieldAttribute

```
public Format.Field getFieldAttribute()
```

Returns the field identifier as an attribute constant from one of the `Field` subclasses. May return null if the field is specified only by an integer field ID.

Returns:

Identifier for the field

Since:

1.4

getField

```
public int getField()
```

Retrieves the field identifier.

Returns:

the field identifier

getBeginIndex

```
public int getBeginIndex()
```

Retrieves the index of the first character in the requested field.

Returns:

the begin index

getEndIndex

```
public int getEndIndex()
```

Retrieves the index of the character following the last character in the requested field.

Returns:

the end index

setBeginIndex

```
public void setBeginIndex(int bi)
```

Sets the begin index. For use by subclasses of Format.

Parameters:

`bi` - the begin index

Since:

1.2

setEndIndex

```
public void setEndIndex(int ei)
```

Sets the end index. For use by subclasses of Format.

Parameters:

`ei` - the end index

Since:

1.2

equals

```
public boolean equals(Object obj)
```

Overrides equals

Overrides:

`equals` in class `Object`

Parameters:

`obj` - the reference object with which to compare.

Returns:

`true` if this object is the same as the obj argument; `false` otherwise.

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public int hashCode()
```

Returns a hash code for this FieldPosition.

Overrides:

`hashCode` in class `Object`

Returns:

a hash code for this FieldPosition

See Also:

`Object.equals(java.lang.Object)`,
`System.identityHashCode(Object)`

toString

```
public String toString()
```

Return a string representation of this FieldPosition.

Overrides:

`toString` in class `Object`

Returns:

a string representation of this object

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.