JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class Format.Field

java.lang.Object
  java.text.AttributedCharacterIterator.Attribute
    java.text.Format.Field

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

DateFormat.Field, MessageFormat.Field, NumberFormat.Field

Enclosing class:

Format

```
public static class Format.Field
extends AttributedCharacterIterator.Attribute
```

Defines constants that are used as attribute keys in the `AttributedCharacterIterator` returned from `Format.formatToCharacterIterator` and as field identifiers in `FieldPosition`.

Since:

1.4

See Also:

Serialized Form

Field Summary

Fields declared in class AttributedCharacterIterator.Attribute
INPUT_METHOD_SEGMENT, LANGUAGE, READING

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**Field**(String name)	Creates a Field with the specified name.

Method Summary

Methods declared in class AttributedCharacterIterator.Attribute

equals, getName, hashCode, readResolve, toString

Methods declared in class Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Constructor Details

Field

```
protected Field(String name)
```

Creates a Field with the specified name.

Parameters:

name - Name of the attribute

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.