JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class MessageFormat.Field

java.lang.Object
  java.text.AttributedCharacterIterator.Attribute
    java.text.Format.Field
      java.text.MessageFormat.Field

All Implemented Interfaces:

Serializable

Enclosing class:

MessageFormat

```
public static class MessageFormat.Field
extends Format.Field
```

Defines constants that are used as attribute keys in the `AttributedCharacterIterator` returned from `MessageFormat.formatToCharacterIterator`.

Since:

1.4

See Also:

Serialized Form

Field Summary

Fields

Modifier and Type	Field	Description
`static final MessageFormat.Field`	**`ARGUMENT`**	Constant identifying a portion of a message that was generated from an argument passed into `formatToCharacterIterator`.

Fields declared in class AttributedCharacterIterator.Attribute

`INPUT_METHOD_SEGMENT`, `LANGUAGE`, `READING`

Constructor Summary

Constructors

Modifier	Constructor	Description

protected **Field**(String name)	Creates a Field with the specified name.

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
protected Object	**readResolve**()	Resolves instances being deserialized to the predefined constants.

Methods declared in class AttributedCharacterIterator.Attribute

equals, getName, hashCode, toString

Methods declared in class Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Field Details

ARGUMENT

```
public static final MessageFormat.Field ARGUMENT
```

Constant identifying a portion of a message that was generated from an argument passed into `formatToCharacterIterator`. The value associated with the key will be an `Integer` indicating the index in the `arguments` array of the argument from which the text was generated.

Constructor Details

Field

```
protected Field(String name)
```

Creates a Field with the specified name.

Parameters:

`name` - Name of the attribute

Method Details

readResolve

```
protected Object readResolve()
                     throws InvalidObjectException
```

Resolves instances being deserialized to the predefined constants.

Overrides:

`readResolve` in class `AttributedCharacterIterator.Attribute`

Returns:

resolved MessageFormat.Field constant

Throws:

`InvalidObjectException` - if the constant could not be resolved.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.