JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class NumberFormat.Field

java.lang.Object
  java.text.AttributedCharacterIterator.Attribute
    java.text.Format.Field
      java.text.NumberFormat.Field

All Implemented Interfaces:

Serializable

Enclosing class:

NumberFormat

```
public static class NumberFormat.Field
extends Format.Field
```

Defines constants that are used as attribute keys in the `AttributedCharacterIterator` returned from `NumberFormat.formatToCharacterIterator` and as field identifiers in `FieldPosition`.

Since:

1.4

See Also:

Serialized Form

Field Summary

Fields

Modifier and Type	Field	Description
static final NumberFormat.Field	**CURRENCY**	Constant identifying the currency field.
static final NumberFormat.Field	**DECIMAL_SEPARATOR**	Constant identifying the decimal separator field.
static final NumberFormat.Field	**EXPONENT**	Constant identifying the exponent field.
static final NumberFormat.Field	**EXPONENT_SIGN**	Constant identifying the exponent sign field.
static final NumberFormat.Field	**EXPONENT_SYMBOL**	Constant identifying the exponent symbol field.
	FRACTION	

static final NumberFormat.Field		Constant identifying the fraction field.
static final NumberFormat.Field	GROUPING_SEPARATOR	Constant identifying the grouping separator field.
static final NumberFormat.Field	INTEGER	Constant identifying the integer field.
static final NumberFormat.Field	PERCENT	Constant identifying the percent field.
static final NumberFormat.Field	PERMILLE	Constant identifying the permille field.
static final NumberFormat.Field	PREFIX	Constant identifying the prefix field.
static final NumberFormat.Field	SIGN	Constant identifying the sign field.
static final NumberFormat.Field	SUFFIX	Constant identifying the suffix field.

Fields declared in class AttributedCharacterIterator.Attribute

INPUT_METHOD_SEGMENT, LANGUAGE, READING

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	Field(String name)	Creates a Field instance with the specified name.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
protected Object	readResolve()	Resolves instances being deserialized to the predefined constants.

Methods declared in class AttributedCharacterIterator.Attribute

equals, getName, hashCode, toString

Methods declared in class Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Field Details

INTEGER

```
public static final NumberFormat.Field INTEGER
```

Constant identifying the integer field.

FRACTION

```
public static final NumberFormat.Field FRACTION
```

Constant identifying the fraction field.

EXPONENT

```
public static final NumberFormat.Field EXPONENT
```

Constant identifying the exponent field.

DECIMAL_SEPARATOR

```
public static final NumberFormat.Field DECIMAL_SEPARATOR
```

Constant identifying the decimal separator field.

SIGN

```
public static final NumberFormat.Field SIGN
```

Constant identifying the sign field.

GROUPING_SEPARATOR

```
public static final NumberFormat.Field GROUPING_SEPARATOR
```

Constant identifying the grouping separator field.

EXPONENT_SYMBOL

`public static final NumberFormat.Field EXPONENT_SYMBOL`

Constant identifying the exponent symbol field.

PERCENT

`public static final NumberFormat.Field PERCENT`

Constant identifying the percent field.

PERMILLE

`public static final NumberFormat.Field PERMILLE`

Constant identifying the permille field.

CURRENCY

`public static final NumberFormat.Field CURRENCY`

Constant identifying the currency field.

EXPONENT_SIGN

`public static final NumberFormat.Field EXPONENT_SIGN`

Constant identifying the exponent sign field.

PREFIX

`public static final NumberFormat.Field PREFIX`

Constant identifying the prefix field.

Since:

12

SUFFIX

`public static final NumberFormat.Field SUFFIX`

Constant identifying the suffix field.

Since:

12

Constructor Details

Field

```
protected Field(String name)
```

Creates a Field instance with the specified name.

Parameters:

`name` - Name of the attribute

Method Details

readResolve

```
protected Object readResolve()
                     throws InvalidObjectException
```

Resolves instances being deserialized to the predefined constants.

Overrides:

`readResolve` in class `AttributedCharacterIterator.Attribute`

Returns:

resolved NumberFormat.Field constant

Throws:

`InvalidObjectException` - if the constant could not be resolved.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.