JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class ParsePosition

java.lang.Object
    java.text.ParsePosition

```
public class ParsePosition
extends Object
```

`ParsePosition` is a simple class used by `Format` and its subclasses to keep track of the current position during parsing. The `parseObject` method in the various `Format` classes requires a `ParsePosition` object as an argument.

By design, as you parse through a string with different formats, you can use the same `ParsePosition`, since the index parameter records the current position.

Since:

1.1

See Also:

`Format`

Constructor Summary

Constructors

Constructor	Description
`ParsePosition(int index)`	Create a new ParsePosition with the given initial index.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
`boolean`	`equals(Object obj)`	Overrides equals
`int`	`getErrorIndex()`	Retrieve the index at which an error occurred, or -1 if the error index has not been set.
`int`	`getIndex()`	Retrieve the current parse position.
`int`	`hashCode()`	

		Returns a hash code for this ParsePosition.
void	**setErrorIndex**(int ei)	Set the index at which a parse error occurred.
void	**setIndex**(int index)	Set the current parse position.
String	**toString**()	Return a string representation of this ParsePosition.

Methods declared in class Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Constructor Details

ParsePosition

```
public ParsePosition(int index)
```

Create a new ParsePosition with the given initial index.

Parameters:

index - initial index

Method Details

getIndex

```
public int getIndex()
```

Retrieve the current parse position. On input to a parse method, this is the index of the character at which parsing will begin; on output, it is the index of the character following the last character parsed.

Returns:

the current parse position

setIndex

```
public void setIndex(int index)
```

Set the current parse position.

Parameters:

index - the current parse position

setErrorIndex

```
public void setErrorIndex(int ei)
```

Set the index at which a parse error occurred. Formatters should set this before returning an error code from their parseObject method. The default value is -1 if this is not set.

Parameters:

ei - the index at which an error occurred

Since:

1.2

getErrorIndex

```
public int getErrorIndex()
```

Retrieve the index at which an error occurred, or -1 if the error index has not been set.

Returns:

the index at which an error occurred

Since:

1.2

equals

```
public boolean equals(Object obj)
```

Overrides equals

Overrides:

equals in class Object

Parameters:

obj - the reference object with which to compare.

Returns:

true if this object is the same as the obj argument; false otherwise.

See Also:

Object.hashCode(), HashMap

hashCode

```
public int hashCode()
```

Returns a hash code for this ParsePosition.

Overrides:

`hashCode` in class `Object`

Returns:

a hash code for this ParsePosition

See Also:

`Object.equals(java.lang.Object)`,
`System.identityHashCode(Object)`

toString

```
public String toString()
```

Return a string representation of this ParsePosition.

Overrides:

`toString` in class `Object`

Returns:

a string representation of this object

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.