JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class DecimalFormatSymbolsProvider

java.lang.Object
    java.util.spi.LocaleServiceProvider
        java.text.spi.DecimalFormatSymbolsProvider

```
public abstract class DecimalFormatSymbolsProvider
extends LocaleServiceProvider
```

An abstract class for service providers that provide instances of the `DecimalFormatSymbols` class.

The requested `Locale` may contain an extension for specifying the desired numbering system. For example, `"ar-u-nu-arab"` (in the BCP 47 language tag form) specifies Arabic with the Arabic-Indic digits and symbols, while `"ar-u-nu-latn"` specifies Arabic with the Latin digits and symbols. Refer to the *Unicode Locale Data Markup Language (LDML)* specification for numbering systems.

Since:

1.6

See Also:

`Locale.forLanguageTag(String)`, `Locale.getExtension(char)`

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	DecimalFormatSymbolsProv	Sole constructor.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
abstract DecimalFormatSymbols	getInstance (Locale locale)	Returns a new DecimalFormatSymbols instance for the specified locale.

Methods declared in class LocaleServiceProvider

`getAvailableLocales`, `isSupportedLocale`

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

DecimalFormatSymbolsProvider

```
protected DecimalFormatSymbolsProvider()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Details

getInstance

```
public abstract DecimalFormatSymbols getInstance(Locale locale)
```

Returns a new `DecimalFormatSymbols` instance for the specified locale.

Parameters:

`locale` - the desired locale

Returns:

a `DecimalFormatSymbols` instance.

Throws:

`NullPointerException` - if `locale` is null

`IllegalArgumentException` - if `locale` isn't one of the locales returned from `getAvailableLocales()`.

See Also:

`DecimalFormatSymbols.getInstance(java.util.Locale)`

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.