JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class NumberFormatProvider

java.lang.Object
    java.util.spi.LocaleServiceProvider
        java.text.spi.NumberFormatProvider

```
public abstract class NumberFormatProvider
extends LocaleServiceProvider
```

An abstract class for service providers that provide concrete implementations of the `NumberFormat` class.

Since:

1.6

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**NumberFormatProvider**()	Sole constructor.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
NumberFormat	**getCompactNumberInstance**(Locale locale, NumberFormat.Style forma	Returns a new NumberFormat instance which formats a number in its compact form for the specified locale and formatStyle.
abstract NumberFormat	**getCurrencyInstance**(Locale locale)	Returns a new NumberFormat instance which formats monetary values for the specified locale.
abstract NumberFormat	**getIntegerInstance**(Locale locale)	Returns a new NumberFormat instance which formats integer values for the specified locale.

abstract NumberFormat	**getNumberInstance**(Locale locale)	Returns a new general-purpose NumberFormat instance for the specified locale.
abstract NumberFormat	**getPercentInstance**(Locale locale)	Returns a new NumberFormat instance which formats percentage values for the specified locale.

Methods declared in class LocaleServiceProvider

getAvailableLocales, isSupportedLocale

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

NumberFormatProvider

```
protected NumberFormatProvider()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Details

getCurrencyInstance

```
public abstract NumberFormat getCurrencyInstance(Locale locale)
```

Returns a new NumberFormat instance which formats monetary values for the specified locale.

Parameters:

locale - the desired locale.

Returns:

a currency formatter

Throws:

NullPointerException - if locale is null

IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().

See Also:

NumberFormat.getCurrencyInstance(java.util.Locale)

getIntegerInstance

public abstract NumberFormat getIntegerInstance(Locale locale)

Returns a new NumberFormat instance which formats integer values for the specified locale. The returned number format is configured to round floating point numbers to the nearest integer using half-even rounding (see HALF_EVEN) for formatting, and to parse only the integer part of an input string (see isParseIntegerOnly).

Parameters:

locale - the desired locale

Returns:

a number format for integer values

Throws:

NullPointerException - if locale is null

IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().

See Also:

NumberFormat.getIntegerInstance(java.util.Locale)

getNumberInstance

public abstract NumberFormat getNumberInstance(Locale locale)

Returns a new general-purpose NumberFormat instance for the specified locale.

Parameters:

locale - the desired locale

Returns:

a general-purpose number formatter

Throws:

NullPointerException - if locale is null

IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().

See Also:

NumberFormat.getNumberInstance(java.util.Locale)

getPercentInstance

```
public abstract NumberFormat getPercentInstance(Locale locale)
```

Returns a new NumberFormat instance which formats percentage values for the specified locale.

Parameters:

locale - the desired locale

Returns:

a percent formatter

Throws:

NullPointerException - if locale is null

IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().

See Also:

NumberFormat.getPercentInstance(java.util.Locale)

getCompactNumberInstance

```
public NumberFormat getCompactNumberInstance
(Locale locale,
 NumberFormat.Style formatStyle)
```

Returns a new NumberFormat instance which formats a number in its compact form for the specified locale and formatStyle.

Implementation Requirements:

The default implementation of this method throws UnsupportedOperationException. Overriding the implementation of this method returns the compact number formatter instance of the given locale with specified formatStyle.

Parameters:

locale - the desired locale

formatStyle - the style for formatting a number

Returns:

a compact number formatter

Throws:

NullPointerException - if locale or formatStyle is null

`IllegalArgumentException` - if `locale` is not one of the locales returned from `getAvailableLocales()`.

`UnsupportedOperationException` - if the implementation does not support this method

Since:

12

See Also:

`NumberFormat.getCompactNumberInstance(Locale, NumberFormat.Style)`

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.