JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Enum Class HijrahEra

java.lang.Object
  java.lang.Enum<HijrahEra>
    java.time.chrono.HijrahEra

All Implemented Interfaces:

Serializable, Comparable<HijrahEra>, Constable, Era, TemporalAccessor, TemporalAdjuster

---

```
public enum HijrahEra
extends Enum<HijrahEra>
implements Era
```

An era in the Hijrah calendar system.

The Hijrah calendar system has only one era covering the proleptic years greater than zero.

Do not use `ordinal()` to obtain the numeric representation of `HijrahEra`. Use `getValue()` instead.

Implementation Requirements:

This is an immutable and thread-safe enum.

Since:

1.8

Nested Class Summary

Nested classes/interfaces declared in class Enum
Enum.EnumDesc<E>

Enum Constant Summary

Enum Constants

Enum Constant	Description
AH	The singleton instance for the current era, 'Anno Hegirae', which has the numeric value 1.

Method Summary

All Methods | Static Methods

Modifier and Type	Method	Description
String	**getDisplayName**(TextStyle style, Locale locale)	Gets the textual representation of this era.
int	**getValue**()	Gets the numeric era int value.
static HijrahEra	**of**(int hijrahEra)	Obtains an instance of HijrahEra from an int value.
ValueRange	**range**(TemporalField field)	Gets the range of valid values for the specified field.
static HijrahEra	**valueOf**(String name)	Returns the enum constant of this class with the specified name.
static HijrahEra[]	**values**()	Returns an array containing the constants of this enum class, in the order they are declared.

Methods declared in class Enum

clone, compareTo, describeConstable, equals, finalize, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods declared in class Object

getClass, notify, notifyAll, wait, wait, wait

Methods declared in interface Era

adjustInto, get, getLong, isSupported, query

Enum Constant Details

AH

```
public static final HijrahEra AH
```

The singleton instance for the current era, 'Anno Hegirae', which has the numeric value 1.

Method Details

values

`public static HijrahEra[] values()`

Returns an array containing the constants of this enum class, in the order they are declared.

Returns:

an array containing the constants of this enum class, in the order they are declared

valueOf

`public static HijrahEra valueOf(String name)`

Returns the enum constant of this class with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this class. (Extraneous whitespace characters are not permitted.)

Parameters:

`name` - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

`IllegalArgumentException` - if this enum class has no constant with the specified name

`NullPointerException` - if the argument is null

of

`public static HijrahEra of(int hijrahEra)`

Obtains an instance of `HijrahEra` from an `int` value.

The current era, which is the only accepted value, has the value 1

Parameters:

`hijrahEra` - the era to represent, only 1 supported

Returns:

the HijrahEra.AH singleton, not null

Throws:

`DateTimeException` - if the value is invalid

getValue

```
public int getValue()
```

Gets the numeric era `int` value.

The era AH has the value 1.

Specified by:

`getValue` in interface `Era`

Returns:

the era value, 1 (AH)

range

```
public ValueRange range(TemporalField field)
```

Gets the range of valid values for the specified field.

The range object expresses the minimum and maximum valid values for a field. This era is used to enhance the accuracy of the returned range. If it is not possible to return the range, because the field is not supported or for some other reason, an exception is thrown.

If the field is a `ChronoField` then the query is implemented here. The `ERA` field returns the range. All other `ChronoField` instances will throw an `UnsupportedTemporalTypeException`.

If the field is not a `ChronoField`, then the result of this method is obtained by invoking `TemporalField.rangeRefinedBy(TemporalAccessor)` passing `this` as the argument. Whether the range can be obtained is determined by the field.

The `ERA` field returns a range for the one valid Hijrah era.

Specified by:

`range` in interface `Era`

Specified by:

`range` in interface `TemporalAccessor`

Parameters:

`field` - the field to query the range for, not null

Returns:

the range of valid values for the field, not null

Throws:

DateTimeException - if the range for the field cannot be obtained

UnsupportedTemporalTypeException - if the unit is not supported

getDisplayName

```
public String getDisplayName(TextStyle style,
                             Locale locale)
```

Gets the textual representation of this era.

This returns the textual name used to identify the era, suitable for presentation to the user. The parameters control the style of the returned text and the locale.

If no textual mapping is found then the numeric value is returned.

Specified by:

getDisplayName in interface Era

Parameters:

style - the style of the text required, not null

locale - the locale to use, not null

Returns:

the text value of the era, not null

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.