JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Enum Class IsoEra

java.lang.Object
  java.lang.Enum<IsoEra>
    java.time.chrono.IsoEra

All Implemented Interfaces:

Serializable, Comparable<IsoEra>, Constable, Era, TemporalAccessor, TemporalAdjuster

---

```
public enum IsoEra
extends Enum<IsoEra>
implements Era
```

An era in the ISO calendar system.

The ISO-8601 standard does not define eras. A definition has therefore been created with two eras - 'Current era' (CE) for years on or after 0001-01-01 (ISO), and 'Before current era' (BCE) for years before that.

year-of-era	era	proleptic-year
2	CE	2
1	CE	1
1	BCE	0
2	BCE	-1

Do not use `ordinal()` to obtain the numeric representation of `IsoEra`. Use `getValue()` instead.

Implementation Requirements:

This is an immutable and thread-safe enum.

Since:

1.8

Nested Class Summary

Nested classes/interfaces declared in class Enum
Enum.EnumDesc<E>

Enum Constant Summary

Enum Constants

Enum Constant	Description

BCE	The singleton instance for the era before the current one, 'Before Current Era', which has the numeric value 0.
CE	The singleton instance for the current era, 'Current Era', which has the numeric value 1.

Method Summary

All Methods | **Static Methods**

Modifier and Type	Method	Description
`int`	**`getValue`**`()`	Gets the numeric era `int` value.
`static IsoEra`	**`of`**`(int isoEra)`	Obtains an instance of `IsoEra` from an `int` value.
`static IsoEra`	**`valueOf`**`(String name)`	Returns the enum constant of this class with the specified name.
`static IsoEra[]`	**`values`**`()`	Returns an array containing the constants of this enum class, in the order they are declared.

Methods declared in class Enum

`clone`, `compareTo`, `describeConstable`, `equals`, `finalize`, `getDeclaringClass`, `hashCode`, `name`, `ordinal`, `toString`, `valueOf`

Methods declared in class Object

`getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Methods declared in interface Era

`adjustInto`, `get`, `getDisplayName`, `getLong`, `isSupported`, `query`, `range`

Enum Constant Details

BCE

```
public static final IsoEra BCE
```

The singleton instance for the era before the current one, 'Before Current Era', which has the numeric value 0.

CE

```
public static final IsoEra CE
```

The singleton instance for the current era, 'Current Era', which has the numeric value 1.

Method Details

values

```
public static IsoEra[] values()
```

Returns an array containing the constants of this enum class, in the order they are declared.

Returns:

an array containing the constants of this enum class, in the order they are declared

valueOf

```
public static IsoEra valueOf(String name)
```

Returns the enum constant of this class with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this class. (Extraneous whitespace characters are not permitted.)

Parameters:

`name` - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

IllegalArgumentException - if this enum class has no constant with the specified name

NullPointerException - if the argument is null

of

`public static IsoEra of(int isoEra)`

Obtains an instance of `IsoEra` from an `int` value.

`IsoEra` is an enum representing the ISO eras of BCE/CE. This factory allows the enum to be obtained from the `int` value.

Parameters:

`isoEra` - the BCE/CE value to represent, from 0 (BCE) to 1 (CE)

Returns:

the era singleton, not null

Throws:

DateTimeException - if the value is invalid

getValue

`public int getValue()`

Gets the numeric era `int` value.

The era BCE has the value 0, while the era CE has the value 1.

Specified by:

getValue in interface Era

Returns:

the era value, from 0 (BCE) to 1 (CE)

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.