JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Enum Class MinguoEra

java.lang.Object
  java.lang.Enum<MinguoEra>
    java.time.chrono.MinguoEra

All Implemented Interfaces:

Serializable, Comparable<MinguoEra>, Constable, Era, TemporalAccessor, TemporalAdjuster

---

```
public enum MinguoEra
extends Enum<MinguoEra>
implements Era
```

An era in the Minguo calendar system.

The Minguo calendar system has two eras. The current era, for years from 1 onwards, is known as the 'Republic of China' era. All previous years, zero or earlier in the proleptic count or one and greater in the year-of-era count, are part of the 'Before Republic of China' era.

year-of-era	era	proleptic-year	ISO proleptic-year
2	ROC	2	1913
1	ROC	1	1912
1	BEFORE_ROC	0	1911
2	BEFORE_ROC	-1	1910

Do not use `ordinal()` to obtain the numeric representation of `MinguoEra`. Use `getValue()` instead.

Implementation Requirements:

This is an immutable and thread-safe enum.

Since:

1.8

Nested Class Summary

Nested classes/interfaces declared in class Enum
Enum.EnumDesc<E>

Enum Constant Summary

Enum Constants

Enum Constant	Description

BEFORE_ROC	The singleton instance for the era before the current one, 'Before Republic of China Era', which has the numeric value 0.
ROC	The singleton instance for the current era, 'Republic of China Era', which has the numeric value 1.

Method Summary

All Methods | **Static Methods**

Modifier and Type	Method	Description
String	**getDisplayName**(TextStyle style, Locale locale)	Gets the textual representation of this era.
int	**getValue**()	Gets the numeric era int value.
static MinguoEra	**of**(int minguoEra)	Obtains an instance of MinguoEra from an int value.
static MinguoEra	**valueOf**(String name)	Returns the enum constant of this class with the specified name.
static MinguoEra[]	**values**()	Returns an array containing the constants of this enum class, in the order they are declared.

Methods declared in class Enum

clone, compareTo, describeConstable, equals, finalize, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods declared in class Object

getClass, notify, notifyAll, wait, wait, wait

Methods declared in interface Era

`adjustInto`, `get`, `getLong`, `isSupported`, `query`, `range`

Enum Constant Details

BEFORE_ROC

```
public static final MinguoEra BEFORE_ROC
```

The singleton instance for the era before the current one, 'Before Republic of China Era', which has the numeric value 0.

ROC

```
public static final MinguoEra ROC
```

The singleton instance for the current era, 'Republic of China Era', which has the numeric value 1.

Method Details

values

```
public static MinguoEra[] values()
```

Returns an array containing the constants of this enum class, in the order they are declared.

Returns:

an array containing the constants of this enum class, in the order they are declared

valueOf

```
public static MinguoEra valueOf(String name)
```

Returns the enum constant of this class with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this class. (Extraneous whitespace characters are not permitted.)

Parameters:

`name` - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

`IllegalArgumentException` - if this enum class has no constant with the specified name

`NullPointerException` - if the argument is null

of

```
public static MinguoEra of(int minguoEra)
```

Obtains an instance of `MinguoEra` from an `int` value.

`MinguoEra` is an enum representing the Minguo eras of BEFORE_ROC/ROC. This factory allows the enum to be obtained from the `int` value.

Parameters:

`minguoEra` - the BEFORE_ROC/ROC value to represent, from 0 (BEFORE_ROC) to 1 (ROC)

Returns:

the era singleton, not null

Throws:

`DateTimeException` - if the value is invalid

getValue

```
public int getValue()
```

Gets the numeric era `int` value.

The era BEFORE_ROC has the value 0, while the era ROC has the value 1.

Specified by:

`getValue` in interface `Era`

Returns:

the era value, from 0 (BEFORE_ROC) to 1 (ROC)

getDisplayName

```
public String getDisplayName(TextStyle style,
                             Locale locale)
```

Gets the textual representation of this era.

This returns the textual name used to identify the era, suitable for presentation to the user. The parameters control the style of the returned text and the locale.

If no textual mapping is found then the `numeric value` is returned.

Specified by:

`getDisplayName` in interface `Era`

Parameters:

`style` - the style of the text required, not null

`locale` - the locale to use, not null

Returns:

the text value of the era, not null

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.