JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class DecimalStyle

java.lang.Object
    java.time.format.DecimalStyle

```
public final class DecimalStyle
extends Object
```

Localized decimal style used in date and time formatting.

A significant part of dealing with dates and times is the localization. This class acts as a central point for accessing the information.

Implementation Requirements:

This class is immutable and thread-safe.

Since:

1.8

Field Summary

Fields

Modifier and Type	Field	Description
static final DecimalStyle	STANDARD	The standard set of non-localized decimal style symbols.

Method Summary

All Methods | **Static Methods**

Modifier and Type	Method	Description
boolean	equals(Object obj)	Checks if this DecimalStyle is equal to another DecimalStyle.
static Set<Locale>	getAvailableLocales()	Lists all the locales that are supported.
char	getDecimalSeparator()	Gets the character that represents the decimal point.
char	getNegativeSign()	

		Gets the character that represents the negative sign.
char	**getPositiveSign**()	Gets the character that represents the positive sign.
char	**getZeroDigit**()	Gets the character that represents zero.
int	**hashCode**()	A hash code for this DecimalStyle.
static DecimalStyle	**of**(Locale locale)	Obtains the DecimalStyle for the specified locale.
static DecimalStyle	**ofDefaultLocale**()	Obtains the DecimalStyle for the default FORMAT locale.
String	**toString**()	Returns a string describing this DecimalStyle.
DecimalStyle	**withDecimalSeparator**(char decimalSeparator)	Returns a copy of the info with a new character that represents the decimal point.
DecimalStyle	**withNegativeSign**(char negativeSign)	Returns a copy of the info with a new character that represents the negative sign.
DecimalStyle	**withPositiveSign**(char positiveSign)	Returns a copy of the info with a new character that represents the positive sign.
DecimalStyle	**withZeroDigit**(char zeroDigit)	Returns a copy of the info with a new

	character that represents zero.

Methods declared in class Object

`clone`, `finalize`, `getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Field Details

STANDARD

`public static final DecimalStyle STANDARD`

The standard set of non-localized decimal style symbols.

This uses standard ASCII characters for zero, positive, negative and a dot for the decimal point.

Method Details

getAvailableLocales

`public static Set<Locale> getAvailableLocales()`

Lists all the locales that are supported.

At a minimum, the returned `Set` must contain a `Locale` instance equal to `Locale.ROOT` and a `Locale` instance equal to `Locale.US`.

Returns:

a Set of Locales for which localization is supported

ofDefaultLocale

`public static DecimalStyle ofDefaultLocale()`

Obtains the DecimalStyle for the default `FORMAT` locale.

This method provides access to locale sensitive decimal style symbols.

This is equivalent to calling `of(Locale.getDefault(Locale.Category.FORMAT))`.

Returns:

the decimal style, not null

See Also:

`Locale.Category.FORMAT`

of

```
public static DecimalStyle of(Locale locale)
```

Obtains the DecimalStyle for the specified locale.

This method provides access to locale sensitive decimal style symbols. If the locale contains "nu" (Numbering System) and/or "rg" (Region Override) Unicode extensions, returned instance will reflect the values specified with those extensions. If both "nu" and "rg" are specified, the value from the "nu" extension supersedes the implicit one from the "rg" extension.

Parameters:

`locale` - the locale, not null

Returns:

the decimal style, not null

getZeroDigit

```
public char getZeroDigit()
```

Gets the character that represents zero.

The character used to represent digits may vary by culture. This method specifies the zero character to use, which implies the characters for one to nine.

Returns:

the character for zero

withZeroDigit

```
public DecimalStyle withZeroDigit(char zeroDigit)
```

Returns a copy of the info with a new character that represents zero.

The character used to represent digits may vary by culture. This method specifies the zero character to use, which implies the characters for one to nine.

Parameters:

`zeroDigit` - the character for zero

Returns:

a copy with a new character that represents zero, not null

getPositiveSign

```
public char getPositiveSign()
```

Gets the character that represents the positive sign.

The character used to represent a positive number may vary by culture. This method specifies the character to use.

Returns:

the character for the positive sign

withPositiveSign

```
public DecimalStyle withPositiveSign(char positiveSign)
```

Returns a copy of the info with a new character that represents the positive sign.

The character used to represent a positive number may vary by culture. This method specifies the character to use.

Parameters:

`positiveSign` - the character for the positive sign

Returns:

a copy with a new character that represents the positive sign, not null

getNegativeSign

```
public char getNegativeSign()
```

Gets the character that represents the negative sign.

The character used to represent a negative number may vary by culture. This method specifies the character to use.

Returns:

the character for the negative sign

withNegativeSign

```
public DecimalStyle withNegativeSign(char negativeSign)
```

Returns a copy of the info with a new character that represents the negative sign.

The character used to represent a negative number may vary by culture. This method specifies the character to use.

Parameters:

`negativeSign` - the character for the negative sign

Returns:

a copy with a new character that represents the negative sign, not null

getDecimalSeparator

```
public char getDecimalSeparator()
```

Gets the character that represents the decimal point.

The character used to represent a decimal point may vary by culture. This method specifies the character to use.

Returns:

the character for the decimal point

withDecimalSeparator

```
public DecimalStyle withDecimalSeparator(char decimalSeparator)
```

Returns a copy of the info with a new character that represents the decimal point.

The character used to represent a decimal point may vary by culture. This method specifies the character to use.

Parameters:

`decimalSeparator` - the character for the decimal point

Returns:

a copy with a new character that represents the decimal point, not null

equals

```
public boolean equals(Object obj)
```

Checks if this DecimalStyle is equal to another DecimalStyle.

Overrides:

`equals` in class `Object`

Parameters:

`obj` - the object to check, null returns false

Returns:

true if this is equal to the other date

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public int hashCode()
```

A hash code for this DecimalStyle.

Overrides:

`hashCode` in class `Object`

Returns:

a suitable hash code

See Also:

`Object.equals(java.lang.Object)`,
`System.identityHashCode(Object)`

toString

```
public String toString()
```

Returns a string describing this DecimalStyle.

Overrides:

`toString` in class `Object`

Returns:

a string description, not null

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.