JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class Base64.Encoder

java.lang.Object
    java.util.Base64.Encoder

Enclosing class:

Base64

```
public static class Base64.Encoder
extends Object
```

This class implements an encoder for encoding byte data using the Base64 encoding scheme as specified in RFC 4648 and RFC 2045.

Instances of `Base64.Encoder` class are safe for use by multiple concurrent threads.

Unless otherwise noted, passing a `null` argument to a method of this class will cause a `NullPointerException` to be thrown.

If the encoded byte output of the needed size can not be allocated, the encode methods of this class will cause an `OutOfMemoryError` to be thrown.

Since:

1.8

See Also:

`Base64.Decoder`

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
byte[]	**encode**(byte[] src)	Encodes all bytes from the specified byte array into a newly-allocated byte array using the Base64 encoding scheme.
int	**encode**(byte[] src, byte[] dst)	Encodes all bytes from the specified byte array using the Base64 encoding scheme, writing the resulting bytes to the given output

		byte array, starting at offset 0.
ByteBuffer	**encode**(ByteBuffer buffer)	Encodes all remaining bytes from the specified byte buffer into a newly-allocated ByteBuffer using the Base64 encoding scheme.
String	**encodeToString**(byte[] src)	Encodes the specified byte array into a String using the Base64 encoding scheme.
Base64.Encoder	**withoutPadding**()	Returns an encoder instance that encodes equivalently to this one, but without adding any padding character at the end of the encoded byte data.
OutputStream	**wrap**(OutputStream os)	Wraps an output stream for encoding byte data using the Base64 encoding scheme.

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Method Details

encode

```
public byte[] encode(byte[] src)
```

Encodes all bytes from the specified byte array into a newly-allocated byte array using the Base64 encoding scheme. The returned byte array is of the length of the resulting bytes.

Parameters:

`src` - the byte array to encode

Returns:

A newly-allocated byte array containing the resulting encoded bytes.

encode

```
public int encode(byte[] src,
                  byte[] dst)
```

Encodes all bytes from the specified byte array using the Base64 encoding scheme, writing the resulting bytes to the given output byte array, starting at offset 0.

It is the responsibility of the invoker of this method to make sure the output byte array `dst` has enough space for encoding all bytes from the input byte array. No bytes will be written to the output byte array if the output byte array is not big enough.

Parameters:

`src` - the byte array to encode

`dst` - the output byte array

Returns:

The number of bytes written to the output byte array

Throws:

`IllegalArgumentException` - if `dst` does not have enough space for encoding all input bytes.

encodeToString

```
public String encodeToString(byte[] src)
```

Encodes the specified byte array into a String using the Base64 encoding scheme.

This method first encodes all input bytes into a base64 encoded byte array and then constructs a new String by using the encoded byte array and the `ISO-8859-1` charset.

In other words, an invocation of this method has exactly the same effect as invoking `new String(encode(src), StandardCharsets.ISO_8859_1)`.

Parameters:

`src` - the byte array to encode

Returns:

A String containing the resulting Base64 encoded characters

encode

```
public ByteBuffer encode(ByteBuffer buffer)
```

Encodes all remaining bytes from the specified byte buffer into a newly-allocated ByteBuffer using the Base64 encoding scheme. Upon return, the source buffer's position will be updated to its limit; its limit will not have been changed. The returned output buffer's position will be zero and its limit will be the number of resulting encoded bytes.

Parameters:

`buffer` - the source ByteBuffer to encode

Returns:

A newly-allocated byte buffer containing the encoded bytes.

wrap

```
public OutputStream wrap(OutputStream os)
```

Wraps an output stream for encoding byte data using the Base64 encoding scheme.

It is recommended to promptly close the returned output stream after use, during which it will flush all possible leftover bytes to the underlying output stream. Closing the returned output stream will close the underlying output stream.

Parameters:

`os` - the output stream.

Returns:

the output stream for encoding the byte data into the specified Base64 encoded format

withoutPadding

```
public Base64.Encoder withoutPadding()
```

Returns an encoder instance that encodes equivalently to this one, but without adding any padding character at the end of the encoded byte data.

The encoding scheme of this encoder instance is unaffected by this invocation. The returned encoder instance should be used for non-padding encoding operation.

Returns:

an equivalent encoder that encodes without adding any padding character at the end

---

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.