JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class EventObject

java.lang.Object
    java.util.EventObject

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

AppEvent, AWTEvent, BeanContextEvent, CaretEvent, ChangeEvent, ConnectionEvent, DragGestureEvent, DragSourceEvent, DropTargetEvent, FlavorEvent, HandshakeCompletedEvent, HyperlinkEvent, LineEvent, ListDataEvent, ListSelectionEvent, MenuEvent, NamingEvent, NamingExceptionEvent, NodeChangeEvent, Notification, PopupMenuEvent, PreferenceChangeEvent, PrintEvent, PropertyChangeEvent, RowSetEvent, RowSorterEvent, SSLSessionBindingEvent, StatementEvent, TableColumnModelEvent, TableModelEvent, TreeExpansionEvent, TreeModelEvent, TreeSelectionEvent, UndoableEditEvent, UnsolicitedNotificationEvent

---

```
public class EventObject
extends Object
implements Serializable
```

The root class from which all event state objects shall be derived.

All Events are constructed with a reference to the object, the "source", that is logically deemed to be the object upon which the Event in question initially occurred upon.

Since:

1.1

See Also:

Serialized Form

Field Summary

Fields

Modifier and Type	Field	Description
protected Object	**source**	The object on which the Event initially occurred.

Constructor Summary

Constructors

Constructor	Description
`EventObject(Object source)`	Constructs a prototypical Event.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
`Object`	`getSource()`	The object on which the Event initially occurred.
`String`	`toString()`	Returns a String representation of this EventObject.

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Field Details

source

```
protected transient Object source
```

The object on which the Event initially occurred.

Constructor Details

EventObject

```
public EventObject(Object source)
```

Constructs a prototypical Event.

Parameters:

`source` - the object on which the Event initially occurred

Throws:

`IllegalArgumentException` - if source is null

Method Details

getSource

```
public Object getSource()
```

The object on which the Event initially occurred.

Returns:

the object on which the Event initially occurred

toString

```
public String toString()
```

Returns a String representation of this EventObject.

Overrides:

`toString` in class `Object`

Returns:

a String representation of this EventObject

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.