JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Enum Class Formatter.BigDecimalLayoutForm

java.lang.Object
  java.lang.Enum<Formatter.BigDecimalLayoutForm>
    java.util.Formatter.BigDecimalLayoutForm

All Implemented Interfaces:

Serializable, Comparable<Formatter.BigDecimalLayoutForm>, Constable

Enclosing class:

Formatter

```
public static enum Formatter.BigDecimalLayoutForm
extends Enum<Formatter.BigDecimalLayoutForm>
```

Enum for `BigDecimal` formatting.

Since:

1.5

Nested Class Summary

Nested classes/interfaces declared in class Enum
Enum.EnumDesc<E>

Enum Constant Summary

Enum Constants

Enum Constant	Description
DECIMAL_FLOAT	Format the `BigDecimal` as a decimal number.
SCIENTIFIC	Format the `BigDecimal` in computerized scientific notation.

Method Summary

All Methods | **Static Methods**

Modifier and Type	Method	Description
static Formatter.BigDecimalL	valueOf(String name)	Returns the enum constant of this class with the specified name.

static Formatter.BigDecimal	values()	Returns an array containing the constants of this enum class, in the order they are declared.

Methods declared in class Enum

clone, compareTo, describeConstable, equals, finalize, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods declared in class Object

getClass, notify, notifyAll, wait, wait, wait

Enum Constant Details

SCIENTIFIC

```
public static final Formatter.BigDecimalLayoutForm SCIENTIFIC
```

Format the `BigDecimal` in computerized scientific notation.

DECIMAL_FLOAT

```
public static final Formatter.BigDecimalLayoutForm DECIMAL_FLOAT
```

Format the `BigDecimal` as a decimal number.

Method Details

values

```
public static Formatter.BigDecimalLayoutForm[] values()
```

Returns an array containing the constants of this enum class, in the order they are declared.

Returns:

an array containing the constants of this enum class, in the order they are declared

valueOf

```
public static Formatter.BigDecimalLayoutForm valueOf(String name)
```

Returns the enum constant of this class with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this class. (Extraneous whitespace characters are not permitted.)

Parameters:

`name` - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

`IllegalArgumentException` - if this enum class has no constant with the specified name

`NullPointerException` - if the argument is null

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.