JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class IllegalFormatConversionException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.IllegalArgumentException
          java.util.IllegalFormatException
            java.util.IllegalFormatConversionException

All Implemented Interfaces:

Serializable

```
public non-sealed class IllegalFormatConversionException
extends IllegalFormatException
```

Unchecked exception thrown when the argument corresponding to the format specifier is of an incompatible type.

Unless otherwise specified, passing a `null` argument to any method or constructor in this class will cause a `NullPointerException` to be thrown.

Since:

1.5

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
IllegalFormatConversionException(char c, Class<?> arg)	Constructs an instance of this class with the mismatched conversion and the corresponding argument class.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
Class<?>	**getArgumentClass**()	Returns the class of the mismatched argument.
char	**getConversion**()	Returns the inapplicable conversion.

Methods declared in class Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Details

IllegalFormatConversionException

```
public IllegalFormatConversionException(char c,
                                        Class<?> arg)
```

Constructs an instance of this class with the mismatched conversion and the corresponding argument class.

Parameters:

`c` - Inapplicable conversion

`arg` - Class of the mismatched argument

Method Details

getConversion

```
public char getConversion()
```

Returns the inapplicable conversion.

Returns:

The inapplicable conversion

getArgumentClass

```
public Class<?> getArgumentClass()
```

Returns the class of the mismatched argument.

Returns:

The class of the mismatched argument

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.