JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class IllformedLocaleException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.util.IllformedLocaleException

All Implemented Interfaces:

Serializable

```
public class IllformedLocaleException
extends RuntimeException
```

Thrown by methods in `Locale` and `Locale.Builder` to indicate that an argument is not a well-formed BCP 47 tag.

Since:

1.7

See Also:

`Locale`, Serialized Form

Constructor Summary

Constructors

Constructor	Description
`IllformedLocaleException()`	Constructs a new `IllformedLocaleException` with no detail message and -1 as the error index.
`IllformedLocaleException (String message)`	Constructs a new `IllformedLocaleException` with the given message and -1 as the error index.
`IllformedLocaleException (String message, int errorIndex)`	Constructs a new `IllformedLocaleException` with the given message and the error index.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description

int	**getErrorIndex**()	Returns the index where the error was found.

Methods declared in class Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Details

IllformedLocaleException

```
public IllformedLocaleException()
```

Constructs a new IllformedLocaleException with no detail message and -1 as the error index.

IllformedLocaleException

```
public IllformedLocaleException(String message)
```

Constructs a new IllformedLocaleException with the given message and -1 as the error index.

Parameters:

message - the message

IllformedLocaleException

```
public IllformedLocaleException(String message,
                                int errorIndex)
```

Constructs a new IllformedLocaleException with the given message and the error index. The error index is the approximate offset from the start of the ill-formed value to the point where the parse first detected an error. A negative error index value indicates either the error index is not applicable or unknown.

Parameters:

`message` - the message

`errorIndex` - the index

Method Details

getErrorIndex

```
public int getErrorIndex()
```

Returns the index where the error was found. A negative value indicates either the error index is not applicable or unknown.

Returns:

the error index

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.