JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class ListResourceBundle

java.lang.Object
    java.util.ResourceBundle
        java.util.ListResourceBundle

Direct Known Subclasses:

AccessibleResourceBundle

---

public abstract class **ListResourceBundle**
extends ResourceBundle

ListResourceBundle is an abstract subclass of ResourceBundle that manages resources for a locale in a convenient and easy to use list. See ResourceBundle for more information about resource bundles in general.

Subclasses must override getContents and provide an array, where each item in the array is a pair of objects. The first element of each pair is the key, which must be a String,
and the second element is the value associated with that key.

The following example shows two members of a resource bundle family with the base name "MyResources". "MyResources" is the default member of the bundle family, and "MyResources_fr" is the French member. These members are based on ListResourceBundle (a related example shows how you can add a bundle to this family that's based on a properties file). The keys in this example are of the form "s1" etc. The actual keys are entirely up to your choice, so long as they are the same as the keys you use in your program to retrieve the objects from the bundle. Keys are case-sensitive.

```
public class MyResources extends ListResourceBundle {
    protected Object[][] getContents() {
        return new Object[][] {
        // LOCALIZE THIS
            {"s1", "The disk \"{1}\" contains {0}."},  // MessageFormat pattern
            {"s2", "1"},                               // location of {0} in patt
            {"s3", "My Disk"},                         // sample disk name
            {"s4", "no files"},                        // first ChoiceFormat choi
            {"s5", "one file"},                        // second ChoiceFormat cho
            {"s6", "{0,number} files"},                // third ChoiceFormat choi
            {"s7", "3 Mar 96"},                        // sample date
            {"s8", new Dimension(1,5)}                 // real object, not just s
        // END OF MATERIAL TO LOCALIZE
        };
    }
```

```
}

public class MyResources_fr extends ListResourceBundle {
    protected Object[][] getContents() {
        return new Object[][] {
        // LOCALIZE THIS
            {"s1", "Le disque \"{1}\" {0}."},         // MessageFormat pattern
            {"s2", "1"},                              // location of {0} in patt
            {"s3", "Mon disque"},                     // sample disk name
            {"s4", "ne contient pas de fichiers"},    // first ChoiceFormat choi
            {"s5", "contient un fichier"},            // second ChoiceFormat cho
            {"s6", "contient {0,number} fichiers"},   // third ChoiceFormat choi
            {"s7", "3 mars 1996"},                    // sample date
            {"s8", new Dimension(1,3)}                // real object, not just s
        // END OF MATERIAL TO LOCALIZE
        };
    }
}
```

The implementation of a `ListResourceBundle` subclass must be thread-safe if it's simultaneously used by multiple threads. The default implementations of the methods in this class are thread-safe.

Since:

1.1

See Also:

`ResourceBundle`, `PropertyResourceBundle`

Nested Class Summary

Nested classes/interfaces declared in class ResourceBundle
`ResourceBundle.Control`

Field Summary

Fields declared in class ResourceBundle
`parent`

Constructor Summary

Constructors

Constructor	Description
`ListResourceBundle()`	Sole constructor.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
protected abstract Object[][]	`getContents()`	Returns an array in which each item is a pair of objects in an `Object` array.
Enumeration<String>	`getKeys()`	Returns an `Enumeration` of the keys contained in this `ResourceBundle` and its parent bundles.
final Object	`handleGetObject(String key)`	Gets an object for the given key from this resource bundle.
protected Set<String>	`handleKeySet()`	Returns a `Set` of the keys contained *only* in this `ResourceBundle`.

Methods declared in class ResourceBundle

clearCache, clearCache, containsKey, getBaseBundleName, getBundle, getBundle, getBundle, getBundle, getBundle, getBundle, getBundle, getBundle, getLocale, getObject, getString, getStringArray, keySet, setParent

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Details

ListResourceBundle

```
public ListResourceBundle()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Details

handleGetObject

```
public final Object handleGetObject(String key)
```

Description copied from class: `ResourceBundle`

Gets an object for the given key from this resource bundle. Returns null if this resource bundle does not contain an object for the given key.

Specified by:

`handleGetObject` in class `ResourceBundle`

Parameters:

key - the key for the desired object

Returns:

the object for the given key, or null

getKeys

```
public Enumeration<String> getKeys()
```

Returns an `Enumeration` of the keys contained in this `ResourceBundle` and its parent bundles.

Specified by:

`getKeys` in class `ResourceBundle`

Returns:

an `Enumeration` of the keys contained in this `ResourceBundle` and its parent bundles.

See Also:

`ResourceBundle.keySet()`

handleKeySet

```
protected Set<String> handleKeySet()
```

Returns a `Set` of the keys contained *only* in this `ResourceBundle`.

Overrides:

`handleKeySet` in class `ResourceBundle`

Returns:

a `Set` of the keys contained only in this `ResourceBundle`

Since:

1.6

See Also:

`ResourceBundle.keySet()`

getContents

```
protected abstract Object[][] getContents()
```

Returns an array in which each item is a pair of objects in an `Object` array. The first element of each pair is the key, which must be a `String`, and the second element is the value associated with that key. See the class description for details.

Returns:

an array of an `Object` array representing a key-value pair.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.