JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Enum Class Locale.FilteringMode

java.lang.Object
    java.lang.Enum<Locale.FilteringMode>
        java.util.Locale.FilteringMode

All Implemented Interfaces:

Serializable, Comparable<Locale.FilteringMode>, Constable

Enclosing class:

Locale

```
public static enum Locale.FilteringMode
extends Enum<Locale.FilteringMode>
```

This enum provides constants to select a filtering mode for locale matching. Refer to RFC 4647 Matching of Language Tags for details.

As an example, think of two Language Priority Lists each of which includes only one language range and a set of following language tags:

```
de (German)
de-DE (German, Germany)
de-Deva (German, in Devanagari script)
de-Deva-DE (German, in Devanagari script, Germany)
de-DE-1996 (German, Germany, orthography of 1996)
de-Latn-DE (German, in Latin script, Germany)
de-Latn-DE-1996 (German, in Latin script, Germany, orthography of 1996)
```

The filtering method will behave as follows:

Filtering method behavior

Filtering Mode	Language Priority List: "de-DE"	Language Priority List: "de-*-DE"
AUTOSELECT_FILTERING	Performs *basic* filtering and returns "de-DE" and "de-DE-1996".	Performs *extended* filtering and returns "de-DE", "de-Deva-DE", "de-DE-1996", "de-Latn-DE", and "de-Latn-DE-1996".
EXTENDED_FILTERING	Performs *extended* filtering and returns "de-DE", "de-Deva-DE", "de-	Same as above.

Filtering Mode	Language Priority List: "de-DE"	Language Priority List: "de-*-DE"
	DE-1996", "de-Latn-DE", and "de-Latn-DE-1996".	
IGNORE_EXTENDED_RANGES	Performs *basic* filtering and returns "de-DE" and "de-DE-1996".	Performs *basic* filtering and returns null because nothing matches.
MAP_EXTENDED_RANGES	Same as above.	Performs *basic* filtering and returns "de-DE" and "de-DE-1996" because "de-*-DE" is mapped to "de-DE".
REJECT_EXTENDED_RANGES	Same as above.	Throws IllegalArgumentException because "de-*-DE" is not a valid basic language range.

Since:

1.8

External Specifications

RFC 4647: Matching of Language Tags

See Also:

Locale.filter(List, Collection, FilteringMode), Locale.filterTags(List, Collection, FilteringMode)

Nested Class Summary

Nested classes/interfaces declared in class Enum
Enum.EnumDesc<E>

Enum Constant Summary

Enum Constants

Enum Constant	Description
AUTOSELECT_FILTERING	Specifies automatic filtering mode based on the given Language

	Priority List consisting of language ranges.
EXTENDED_FILTERING	Specifies extended filtering.
IGNORE_EXTENDED_RANGES	Specifies basic filtering: Note that any extended language ranges included in the given Language Priority List are ignored.
MAP_EXTENDED_RANGES	Specifies basic filtering: If any extended language ranges are included in the given Language Priority List, they are mapped to the basic language range.
REJECT_EXTENDED_RANGES	Specifies basic filtering: If any extended language ranges are included in the given Language Priority List, the list is rejected and the filtering method throws `IllegalArgumentException`.

Method Summary

All Methods | **Static Methods**

Modifier and Type	Method	Description
static `Locale.FilteringMode`	**valueOf**(`String` name)	Returns the enum constant of this class with the specified name.
static `Locale.FilteringMode`	**values**()	Returns an array containing the constants of this enum class, in the order they are declared.

Methods declared in class Enum

`clone`, `compareTo`, `describeConstable`, `equals`, `finalize`, `getDeclaringClass`, `hashCode`, `name`, `ordinal`, `toString`, `valueOf`

Methods declared in class Object

`getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Enum Constant Details

AUTOSELECT_FILTERING

`public static final Locale.FilteringMode AUTOSELECT_FILTERING`

Specifies automatic filtering mode based on the given Language Priority List consisting of language ranges. If all of the ranges are basic, basic filtering is selected. Otherwise, extended filtering is selected.

EXTENDED_FILTERING

`public static final Locale.FilteringMode EXTENDED_FILTERING`

Specifies extended filtering.

IGNORE_EXTENDED_RANGES

`public static final Locale.FilteringMode IGNORE_EXTENDED_RANGES`

Specifies basic filtering: Note that any extended language ranges included in the given Language Priority List are ignored.

MAP_EXTENDED_RANGES

`public static final Locale.FilteringMode MAP_EXTENDED_RANGES`

Specifies basic filtering: If any extended language ranges are included in the given Language Priority List, they are mapped to the basic language range. Specifically, a language range starting with a subtag `"*"` is treated as a language range `"*"`. For example, `"*-US"` is treated as `"*"`. If `"*"` is not the first subtag, `"*"` and extra `"-"` are removed. For example, `"ja-*-JP"` is mapped to `"ja-JP"`.

REJECT_EXTENDED_RANGES

`public static final Locale.FilteringMode REJECT_EXTENDED_RANGES`

Specifies basic filtering: If any extended language ranges are included in the given Language Priority List, the list is rejected and the filtering method throws `IllegalArgumentException`.

Method Details

values

`public static Locale.FilteringMode[] values()`

Returns an array containing the constants of this enum class, in the order they are declared.

Returns:

an array containing the constants of this enum class, in the order they are declared

valueOf

`public static Locale.FilteringMode valueOf(String name)`

Returns the enum constant of this class with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this class. (Extraneous whitespace characters are not permitted.)

Parameters:

`name` - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

`IllegalArgumentException` - if this enum class has no constant with the specified name

`NullPointerException` - if the argument is null

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.