JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class PropertyResourceBundle

java.lang.Object
    java.util.ResourceBundle
        java.util.PropertyResourceBundle

```
public class PropertyResourceBundle
extends ResourceBundle
```

`PropertyResourceBundle` is a concrete subclass of `ResourceBundle` that manages resources for a locale using a set of static strings from a property file. See `ResourceBundle` for more information about resource bundles.

Unlike other types of resource bundle, you don't subclass `PropertyResourceBundle`. Instead, you supply properties files containing the resource data. `ResourceBundle.getBundle` will automatically look for the appropriate properties file and create a `PropertyResourceBundle` that refers to it. See `ResourceBundle.getBundle` for a complete description of the search and instantiation strategy.

The following example shows a member of a resource bundle family with the base name "MyResources". The text defines the bundle "MyResources_de", the German member of the bundle family. This member is based on `PropertyResourceBundle`, and the text therefore is the content of the file "MyResources_de.properties" (a related example shows how you can add bundles to this family that are implemented as subclasses of `ListResourceBundle`). The keys in this example are of the form "s1" etc. The actual keys are entirely up to your choice, so long as they are the same as the keys you use in your program to retrieve the objects from the bundle. Keys are case-sensitive.

```
    # MessageFormat pattern
    s1=Die Platte \"{1}\" enthält {0}.
    # location of {0} in pattern
    s2=1
    # sample disk name
    s3=Meine Platte
    # first ChoiceFormat choice
    s4=keine Dateien
    # second ChoiceFormat choice
    s5=eine Datei
    # third ChoiceFormat choice
    s6={0,number} Dateien
    # sample date
    s7=3. März 1996
```

API Note:

`PropertyResourceBundle` can be constructed either from an `InputStream` or a `Reader`, which represents a property file. Constructing a `PropertyResourceBundle` instance from an `InputStream` requires that the input stream be encoded in `UTF-8`. By default, if a `MalformedInputException` or an `UnmappableCharacterException` occurs on reading the input stream, then the `PropertyResourceBundle` instance resets to the state before the exception, re-reads the input stream in `ISO-8859-1`, and continues reading. If the system property `java.util.PropertyResourceBundle.encoding` is set to either "ISO-8859-1" or "UTF-8", the input stream is solely read in that encoding, and throws the exception if it encounters an invalid sequence. If "ISO-8859-1" is specified, characters that cannot be represented in ISO-8859-1 encoding must be represented by Unicode Escapes as defined in section §3.3 of *The Java Language Specification* whereas the other constructor which takes a `Reader` does not have that limitation. Other encoding values are ignored for this system property. The system property is read and evaluated when initializing this class. Changing or removing the property has no effect after the initialization.

Implementation Requirements:

The implementation of a `PropertyResourceBundle` subclass must be thread-safe if it's simultaneously used by multiple threads. The default implementations of the non-abstract methods in this class are thread-safe.

Since:

1.1

See Also:

`ResourceBundle`, `ListResourceBundle`, `Properties`

Nested Class Summary

Nested classes/interfaces declared in class ResourceBundle
`ResourceBundle.Control`

Field Summary

Fields declared in class ResourceBundle
`parent`

Constructor Summary

Constructors

Constructor	Description
PropertyResourceBundle(InputStream stream)	Creates a property resource bundle from an InputStream.
PropertyResourceBundle(Reader reader)	Creates a property resource bundle from a Reader.

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
Enumeration<String>	**getKeys**()	Returns an Enumeration of the keys contained in this ResourceBundle and its parent bundles.
Object	**handleGetObject**(String key)	Gets an object for the given key from this resource bundle.
protected Set<String>	**handleKeySet**()	Returns a Set of the keys contained *only* in this ResourceBundle.

Methods declared in class ResourceBundle

clearCache, clearCache, containsKey, getBaseBundleName, getBundle, getBundle, getBundle, getBundle, getBundle, getBundle, getBundle, getBundle, getLocale, getObject, getString, getStringArray, keySet, setParent

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

PropertyResourceBundle

```
public PropertyResourceBundle(InputStream stream)
                       throws IOException
```

Creates a property resource bundle from an `InputStream`. This constructor reads the property file in UTF-8 by default. If a `MalformedInputException` or an `UnmappableCharacterException` occurs on reading the input stream, then the PropertyResourceBundle instance resets to the state before the exception, re-reads the input stream in `ISO-8859-1` and continues reading. If the system property `java.util.PropertyResourceBundle.encoding` is set to either "ISO-8859-1" or "UTF-8", the input stream is solely read in that encoding, and throws the exception if it encounters an invalid sequence. Other encoding values are ignored for this system property. The system property is read and evaluated when initializing this class. Changing or removing the property has no effect after the initialization.

Parameters:

`stream` - an InputStream that represents a property file to read from.

Throws:

`IOException` - if an I/O error occurs

`NullPointerException` - if `stream` is null

`IllegalArgumentException` - if `stream` contains a malformed Unicode escape sequence.

`MalformedInputException` - if the system property `java.util.PropertyResourceBundle.encoding` is set to "UTF-8" and `stream` contains an invalid UTF-8 byte sequence.

`UnmappableCharacterException` - if the system property `java.util.PropertyResourceBundle.encoding` is set to "UTF-8" and `stream` contains an unmappable UTF-8 byte sequence.

PropertyResourceBundle

```
public PropertyResourceBundle(Reader reader)
                       throws IOException
```

Creates a property resource bundle from a `Reader`. Unlike the constructor `PropertyResourceBundle(InputStream)`, there is no limitation as to the encoding of the input property file.

Parameters:

`reader` - a Reader that represents a property file to read from.

Throws:

`IOException` - if an I/O error occurs

`NullPointerException` - if `reader` is null

`IllegalArgumentException` - if a malformed Unicode escape sequence appears from `reader`.

Since:

1.6

Method Details

handleGetObject

```
public Object handleGetObject(String key)
```

Description copied from class: `ResourceBundle`

Gets an object for the given key from this resource bundle. Returns null if this resource bundle does not contain an object for the given key.

Specified by:

`handleGetObject` in class `ResourceBundle`

Parameters:

key - the key for the desired object

Returns:

the object for the given key, or null

getKeys

```
public Enumeration<String> getKeys()
```

Returns an `Enumeration` of the keys contained in this `ResourceBundle` and its parent bundles.

Specified by:

`getKeys` in class `ResourceBundle`

Returns:

an `Enumeration` of the keys contained in this `ResourceBundle` and its parent bundles.

See Also:

`ResourceBundle.keySet()`

handleKeySet

```
protected Set<String> handleKeySet()
```

Returns a `Set` of the keys contained *only* in this `ResourceBundle`.

Overrides:

`handleKeySet` in class `ResourceBundle`

Returns:

a `Set` of the keys contained only in this `ResourceBundle`

Since:

1.6

See Also:

`ResourceBundle.keySet()`

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.