JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class CompletionException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.util.concurrent.CompletionException

All Implemented Interfaces:

Serializable

```
public class CompletionException
extends RuntimeException
```

Exception thrown when an error or other exception is encountered in the course of completing a result or task.

Since:

1.8

See Also:

Serialized Form

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	`CompletionException()`	Constructs a `CompletionException` with no detail message.
protected	`CompletionException(String message)`	Constructs a `CompletionException` with the specified detail message.
	`CompletionException(String message, Throwable cause)`	Constructs a `CompletionException` with the specified detail message and cause.
	`CompletionException(Throwable cause)`	Constructs a `CompletionException` with the specified cause.

Method Summary

Methods declared in class Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Details

CompletionException

```
protected CompletionException()
```

Constructs a `CompletionException` with no detail message. The cause is not initialized, and may subsequently be initialized by a call to `initCause`.

CompletionException

```
protected CompletionException(String message)
```

Constructs a `CompletionException` with the specified detail message. The cause is not initialized, and may subsequently be initialized by a call to `initCause`.

Parameters:

`message` - the detail message

CompletionException

```
public CompletionException(String message,
                           Throwable cause)
```

Constructs a `CompletionException` with the specified detail message and cause.

Parameters:

`message` - the detail message

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method)

CompletionException

```
public CompletionException(Throwable cause)
```

Constructs a `CompletionException` with the specified cause. The detail message is set to `(cause == null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Parameters:

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method)

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.