JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class ExecutionException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.util.concurrent.ExecutionException

All Implemented Interfaces:

Serializable

```
public class ExecutionException
extends Exception
```

Exception thrown when attempting to retrieve the result of a task that aborted by throwing an exception. This exception can be inspected using the `Throwable.getCause()` method.

Since:

1.5

See Also:

`Future`, Serialized Form

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**ExecutionException**()	Constructs an ExecutionException with no detail message.
protected	**ExecutionException**(String message)	Constructs an ExecutionException with the specified detail message.
	ExecutionException(String message, Throwable cause)	Constructs an ExecutionException with the specified detail message and cause.
	ExecutionException(Throwable cause)	Constructs an ExecutionException with the specified cause.

Method Summary

Methods declared in class Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Details

ExecutionException

```
protected ExecutionException()
```

Constructs an ExecutionException with no detail message. The cause is not initialized, and may subsequently be initialized by a call to initCause.

ExecutionException

```
protected ExecutionException(String message)
```

Constructs an ExecutionException with the specified detail message. The cause is not initialized, and may subsequently be initialized by a call to initCause.

Parameters:

message - the detail message

ExecutionException

```
public ExecutionException(String message,
                          Throwable cause)
```

Constructs an ExecutionException with the specified detail message and cause.

Parameters:

message - the detail message

cause - the cause (which is saved for later retrieval by the Throwable.getCause() method)

ExecutionException

```
public ExecutionException(Throwable cause)
```

Constructs an `ExecutionException` with the specified cause. The detail message is set to `(cause == null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Parameters:

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method)

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.