JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface RunnableFuture<V>

Type Parameters:

V - The result type returned by this Future's get method

All Superinterfaces:

Future<V>, Runnable

All Known Subinterfaces:

RunnableScheduledFuture<V>

All Known Implementing Classes:

FutureTask, SwingWorker

```
public interface RunnableFuture<V>
extends Runnable, Future<V>
```

A Future that is Runnable. Successful execution of the run method causes completion of the Future and allows access to its results.

Since:

1.6

See Also:

FutureTask, Executor

Nested Class Summary

Nested classes/interfaces declared in interface Future
Future.State

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
void	run()	Sets this Future to the result of its computation unless it has been cancelled (or has already been invoked, in which case effects are undefined).

Methods declared in interface Future

`cancel`, `exceptionNow`, `get`, `get`, `isCancelled`, `isDone`, `resultNow`, `state`

Method Details

run

```
void run()
```

Sets this Future to the result of its computation unless it has been cancelled (or has already been invoked, in which case effects are undefined).

Specified by:

`run` in interface `Runnable`

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.