JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface ThreadFactory

`public interface ThreadFactory`

An object that creates new threads on demand. Using thread factories removes hardwiring of calls to `new Thread`, enabling applications to use special thread subclasses, priorities, etc.

The simplest implementation of this interface is just:

```
class SimpleThreadFactory implements ThreadFactory {
  public Thread newThread(Runnable r) {
    return new Thread(r);
  }
}
```

The `Executors.defaultThreadFactory()` method provides a more useful simple implementation, that sets the created thread context to known values before returning it.

Since:

1.5

See Also:

`Thread.Builder.factory()`

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
`Thread`	**`newThread`**`(Runnable r)`	Constructs a new unstarted `Thread` to run the given runnable.

Method Details

newThread

`Thread newThread(Runnable r)`

Constructs a new unstarted `Thread` to run the given runnable.

Parameters:

`r` - a runnable to be executed by new thread instance

Returns:

constructed thread, or `null` if the request to create a thread is rejected

See Also:

Inheritance when creating threads

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.