JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class ThreadPoolExecutor.DiscardOldestPolicy

java.lang.Object
    java.util.concurrent.ThreadPoolExecutor.DiscardOldestPolicy

All Implemented Interfaces:

RejectedExecutionHandler

Enclosing class:

ThreadPoolExecutor

```
public static class ThreadPoolExecutor.DiscardOldestPolicy
extends Object
implements RejectedExecutionHandler
```

A handler for rejected tasks that discards the oldest unhandled request and then retries `execute`, unless the executor is shut down, in which case the task is discarded. This policy is rarely useful in cases where other threads may be waiting for tasks to terminate, or failures must be recorded. Instead consider using a handler of the form:

```
new RejectedExecutionHandler() {
  public void rejectedExecution(Runnable r, ThreadPoolExecutor e) {
    Runnable dropped = e.getQueue().poll();
    if (dropped instanceof Future<?>) {
      ((Future<?>)dropped).cancel(false);
      // also consider logging the failure
    }
    e.execute(r);  // retry
}}
```

Since:

1.5

Constructor Summary

Constructors

Constructor	Description
`DiscardOldestPolicy()`	Creates a `DiscardOldestPolicy` for the given executor.

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
void	**rejectedExecution**(Runnable r, ThreadPoolExecutor e)	Obtains and ignores the next task that the executor would otherwise execute, if one is immediately available, and then retries execution of task r, unless the executor is shut down, in which case task r is instead discarded.

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

DiscardOldestPolicy

```
public DiscardOldestPolicy()
```

Creates a `DiscardOldestPolicy` for the given executor.

Method Details

rejectedExecution

```
public void rejectedExecution(Runnable r,
                              ThreadPoolExecutor e)
```

Obtains and ignores the next task that the executor would otherwise execute, if one is immediately available, and then retries execution of task r, unless the executor is shut down, in which case task r is instead discarded.

Specified by:

`rejectedExecution` in interface `RejectedExecutionHandler`

Parameters:

r - the runnable task requested to be executed

e - the executor attempting to execute this task

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.