JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class AtomicLongFieldUpdater<T>

java.lang.Object
    java.util.concurrent.atomic.AtomicLongFieldUpdater<T>

Type Parameters:

T - The type of the object holding the updatable field

```
public abstract class AtomicLongFieldUpdater<T>
extends Object
```

A reflection-based utility that enables atomic updates to designated non-static `volatile long` fields of designated classes, providing a subset of the functionality of class `VarHandle` that should be used instead. This class is designed for use in atomic data structures in which several fields of the same node are independently subject to atomic updates.

Note that the guarantees of the `compareAndSet` method in this class are weaker than in other atomic classes. Because this class cannot ensure that all uses of the field are appropriate for purposes of atomic access, it can guarantee atomicity only with respect to other invocations of `compareAndSet` and `set` on the same updater.

Object arguments for parameters of type T that are not instances of the class passed to `newUpdater(Class, String)` will result in a `ClassCastException` being thrown.

Since:

1.5

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	`AtomicLongFieldUpdater()`	Protected do-nothing constructor for use by subclasses.

Method Summary

All Methods | **Static Methods**

Modifier and Type	Method	Description
final long		Atomically updates (with memory effects as

	accumulateAndGet(T obj, long x, LongBinaryOperator accum	specified by VarHandle.compareAndSet(Object...)) the field of the given object managed by this updater with the results of applying the given function to the current and given values, returning the updated value.
long	**addAndGet**(T obj, long delta)	Atomically adds the given value to the current value of the field of the given object managed by this updater.
abstract boolean	**compareAndSet**(T obj, long expect, long update)	Atomically sets the field of the given object managed by this updater to the given updated value if the current value == the expected value.
long	**decrementAndGet**(T obj)	Atomically decrements by one the current value of the field of the given object managed by this updater.
abstract long	**get**(T obj)	Returns the current value held in the field of the given object managed by this updater.
final long	**getAndAccumulate**(T obj, long x, LongBinaryOperator accum	Atomically updates (with memory effects as specified by VarHandle.compareAndSet(Object...)) the field of the given

		object managed by this updater with the results of applying the given function to the current and given values, returning the previous value.
long	**getAndAdd**(T obj, long delta)	Atomically adds the given value to the current value of the field of the given object managed by this updater.
long	**getAndDecrement**(T obj)	Atomically decrements by one the current value of the field of the given object managed by this updater.
long	**getAndIncrement**(T obj)	Atomically increments by one the current value of the field of the given object managed by this updater.
long	**getAndSet**(T obj, long newValue)	Atomically sets the field of the given object managed by this updater to the given value and returns the old value.
final long	**getAndUpdate**(T obj, LongUnaryOperator update	Atomically updates (with memory effects as specified by VarHandle.compareAndSet(Object...)) the field of the given object managed by this updater with the results

		of applying the given function, returning the previous value.
long	**incrementAndGet**(T obj)	Atomically increments by one the current value of the field of the given object managed by this updater.
abstract void	**lazySet**(T obj, long newValue)	Eventually sets the field of the given object managed by this updater to the given updated value.
static <U> AtomicLongFieldU <U>	**newUpdater** (Class<U> tclass, String fieldName)	Creates and returns an updater for objects with the given field.
abstract void	**set**(T obj, long newValue)	Sets the field of the given object managed by this updater to the given updated value.
final long	**updateAndGet**(T obj, LongUnaryOperator update	Atomically updates (with memory effects as specified by VarHandle.compareAndSet(Object...)) the field of the given object managed by this updater with the results of applying the given function, returning the updated value.
abstract boolean		Atomically sets the field of the given object managed by this updater

	weakCompareAndSet (T obj, long expect, long update)	to the given updated value if the current value == the expected value.

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

AtomicLongFieldUpdater

```
protected AtomicLongFieldUpdater()
```

Protected do-nothing constructor for use by subclasses.

Method Details

newUpdater

```
public static <U> AtomicLongFieldUpdater<U> newUpdater
(Class<U> tclass,
 String fieldName)
```

Creates and returns an updater for objects with the given field. The Class argument is needed to check that reflective types and generic types match.

Type Parameters:

`U` - the type of instances of tclass

Parameters:

`tclass` - the class of the objects holding the field

`fieldName` - the name of the field to be updated

Returns:

the updater

Throws:

`IllegalArgumentException` - if the field is not a volatile long type

RuntimeException - with a nested reflection-based exception if the class does not hold field or is the wrong type, or the field is inaccessible to the caller according to Java language access control

compareAndSet

```
public abstract boolean compareAndSet(T obj,
                                      long expect,
                                      long update)
```

Atomically sets the field of the given object managed by this updater to the given updated value if the current value == the expected value. This method is guaranteed to be atomic with respect to other calls to `compareAndSet` and `set`, but not necessarily with respect to other changes in the field.

Parameters:

`obj` - An object whose field to conditionally set

`expect` - the expected value

`update` - the new value

Returns:

`true` if successful

weakCompareAndSet

```
public abstract boolean weakCompareAndSet(T obj,
                                          long expect,
                                          long update)
```

Atomically sets the field of the given object managed by this updater to the given updated value if the current value == the expected value. This method is guaranteed to be atomic with respect to other calls to `compareAndSet` and `set`, but not necessarily with respect to other changes in the field.

This operation may fail spuriously and does not provide ordering guarantees, so is only rarely an appropriate alternative to `compareAndSet`.

Parameters:

`obj` - An object whose field to conditionally set

`expect` - the expected value

`update` - the new value

Returns:

`true` if successful

set

```
public abstract void set(T obj,
                         long newValue)
```

Sets the field of the given object managed by this updater to the given updated value. This operation is guaranteed to act as a volatile store with respect to subsequent invocations of `compareAndSet`.

Parameters:

`obj` - An object whose field to set

`newValue` - the new value

lazySet

```
public abstract void lazySet(T obj,
                             long newValue)
```

Eventually sets the field of the given object managed by this updater to the given updated value.

Parameters:

`obj` - An object whose field to set

`newValue` - the new value

Since:

1.6

get

```
public abstract long get(T obj)
```

Returns the current value held in the field of the given object managed by this updater.

Parameters:

`obj` - An object whose field to get

Returns:

the current value

getAndSet

```
public long getAndSet(T obj,
                      long newValue)
```

Atomically sets the field of the given object managed by this updater to the given value and returns the old value.

Parameters:

`obj` - An object whose field to get and set

`newValue` - the new value

Returns:

the previous value

getAndIncrement

```
public long getAndIncrement(T obj)
```

Atomically increments by one the current value of the field of the given object managed by this updater.

Parameters:

`obj` - An object whose field to get and set

Returns:

the previous value

getAndDecrement

```
public long getAndDecrement(T obj)
```

Atomically decrements by one the current value of the field of the given object managed by this updater.

Parameters:

`obj` - An object whose field to get and set

Returns:

the previous value

getAndAdd

```
public long getAndAdd(T obj,
                      long delta)
```

Atomically adds the given value to the current value of the field of the given object managed by this updater.

Parameters:

`obj` - An object whose field to get and set

`delta` - the value to add

Returns:

the previous value

incrementAndGet

```
public long incrementAndGet(T obj)
```

Atomically increments by one the current value of the field of the given object managed by this updater.

Parameters:

`obj` - An object whose field to get and set

Returns:

the updated value

decrementAndGet

```
public long decrementAndGet(T obj)
```

Atomically decrements by one the current value of the field of the given object managed by this updater.

Parameters:

`obj` - An object whose field to get and set

Returns:

the updated value

addAndGet

```
public long addAndGet(T obj,
                      long delta)
```

Atomically adds the given value to the current value of the field of the given object managed by this updater.

Parameters:

`obj` - An object whose field to get and set

`delta` - the value to add

Returns:

the updated value

getAndUpdate

```
public final long getAndUpdate(T obj,
                               LongUnaryOperator updateFunction)
```

Atomically updates (with memory effects as specified by `VarHandle.compareAndSet(Object...)`) the field of the given object managed by this updater with the results of applying the given function, returning the

previous value. The function should be side-effect-free, since it may be re-applied when attempted updates fail due to contention among threads.

Parameters:

`obj` - An object whose field to get and set

`updateFunction` - a side-effect-free function

Returns:

the previous value

Since:

1.8

updateAndGet

```
public final long updateAndGet(T obj,
                               LongUnaryOperator updateFunction)
```

Atomically updates (with memory effects as specified by `VarHandle.compareAndSet(Object...)`) the field of the given object managed by this updater with the results of applying the given function, returning the updated value. The function should be side-effect-free, since it may be re-applied when attempted updates fail due to contention among threads.

Parameters:

`obj` - An object whose field to get and set

`updateFunction` - a side-effect-free function

Returns:

the updated value

Since:

1.8

getAndAccumulate

```
public final long getAndAccumulate
(T obj,
 long x,
 LongBinaryOperator accumulatorFunction)
```

Atomically updates (with memory effects as specified by `VarHandle.compareAndSet(Object...)`) the field of the given object managed by this updater with the results of applying the given function to the current and given values, returning the previous value. The function should be side-effect-free, since it may be re-applied when attempted updates fail due to contention among threads. The function is applied with the current value as its first argument, and the given update as the second argument.

Parameters:

`obj` - An object whose field to get and set

`x` - the update value

`accumulatorFunction` - a side-effect-free function of two arguments

Returns:

the previous value

Since:

1.8

accumulateAndGet

```
public final long accumulateAndGet
(T obj,
 long x,
 LongBinaryOperator accumulatorFunction)
```

Atomically updates (with memory effects as specified by `VarHandle.compareAndSet(Object...)`) the field of the given object managed by this updater with the results of applying the given function to the current and given values, returning the updated value. The function should be side-effect-free, since it may be re-applied when attempted updates fail due to contention among threads. The function is applied with the current value as its first argument, and the given update as the second argument.

Parameters:

`obj` - An object whose field to get and set

`x` - the update value

`accumulatorFunction` - a side-effect-free function of two arguments

Returns:

the updated value

Since:

1.8

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.