JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface IntBinaryOperator

Functional Interface:

This is a functional interface and can therefore be used as the assignment target for a lambda expression or method reference.

```
@FunctionalInterface
public interface IntBinaryOperator
```

Represents an operation upon two `int`-valued operands and producing an `int`-valued result. This is the primitive type specialization of `BinaryOperator` for `int`.

This is a functional interface whose functional method is `applyAsInt(int, int)`.

Since:

1.8

See Also:

`BinaryOperator`, `IntUnaryOperator`

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
`int`	**`applyAsInt`**`(int left, int right)`	Applies this operator to the given operands.

Method Details

applyAsInt

```
int applyAsInt(int left,
               int right)
```

Applies this operator to the given operands.

Parameters:

`left` - the first operand

`right` - the second operand

Returns:

the operator result

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.