JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface LongFunction<R>

Type Parameters:

R - the type of the result of the function

Functional Interface:

This is a functional interface and can therefore be used as the assignment target for a lambda expression or method reference.

```
@FunctionalInterface
public interface LongFunction<R>
```

Represents a function that accepts a long-valued argument and produces a result. This is the `long`-consuming primitive specialization for `Function`.

This is a functional interface whose functional method is `apply(long)`.

Since:

1.8

See Also:

`Function`

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
R	**apply**(long value)	Applies this function to the given argument.

Method Details

apply

```
R apply(long value)
```

Applies this function to the given argument.

Parameters:

`value` - the function argument

Returns:

the function result

---

contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.

Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.

Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.

All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.