JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface LongUnaryOperator

Functional Interface:

This is a functional interface and can therefore be used as the assignment target for a lambda expression or method reference.

```
@FunctionalInterface
public interface LongUnaryOperator
```

Represents an operation on a single `long`-valued operand that produces a `long`-valued result. This is the primitive type specialization of `UnaryOperator` for `long`.

This is a functional interface whose functional method is `applyAsLong(long)`.

Since:

1.8

See Also:

`UnaryOperator`

Method Summary

All Methods	Static Methods	

Modifier and Type	Method	Description
default LongUnaryOperator	**andThen**(LongUnaryOperator after	Returns a composed operator that first applies this operator to its input, and then applies the `after` operator to the result.
long	**applyAsLong**(long operand)	Applies this operator to the given operand.
default LongUnaryOperator	**compose**(LongUnaryOperator befor	Returns a composed operator that first applies the `before` operator to its input, and then applies this operator to the result.
static LongUnaryOperator	**identity**()	Returns a unary operator that always

	returns its input argument.

Method Details

applyAsLong

`long applyAsLong(long operand)`

Applies this operator to the given operand.

Parameters:

`operand` - the operand

Returns:

the operator result

compose

`default LongUnaryOperator compose(LongUnaryOperator before)`

Returns a composed operator that first applies the `before` operator to its input, and then applies this operator to the result. If evaluation of either operator throws an exception, it is relayed to the caller of the composed operator.

Parameters:

`before` - the operator to apply before this operator is applied

Returns:

a composed operator that first applies the `before` operator and then applies this operator

Throws:

`NullPointerException` - if before is null

See Also:

`andThen(LongUnaryOperator)`

andThen

`default LongUnaryOperator andThen(LongUnaryOperator after)`

Returns a composed operator that first applies this operator to its input, and then applies the `after` operator to the result. If evaluation of either operator throws an exception, it is relayed to the caller of the composed operator.

Parameters:

`after` - the operator to apply after this operator is applied

Returns:

a composed operator that first applies this operator and then applies the `after` operator

Throws:

`NullPointerException` - if after is null

See Also:

`compose(LongUnaryOperator)`

identity

```
static LongUnaryOperator identity()
```

Returns a unary operator that always returns its input argument.

Returns:

a unary operator that always returns its input argument

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.