JavaScript is disabled on your browser.

**Java SE 27 & JDK 27**

# Class Attributes.Name

java.lang.Object
    java.util.jar.Attributes.Name

**Enclosing class:**

Attributes

---

```
public static class Attributes.Name
extends Object
```

The Attributes.Name class represents an attribute name stored in this Map. Valid attribute names are case-insensitive, are restricted to the ASCII characters in the set [0-9a-zA-Z_-], and cannot exceed 70 characters in length. Attribute values can contain any characters and will be UTF8-encoded when written to the output stream. See the JAR File Specification for more information about valid attribute names and values.

**Since:**

1.2

**External Specifications**

JAR File Specification

## *Field Summary*

**Fields**

| Modifier and Type | Field | Description |
|---|---|---|
| static final Attributes.Name | CLASS_PATH | Name object for Class-Path manifest attribute. |
| static final Attributes.Name | CONTENT_TYPE | Name object for Content-Type manifest attribute. |
| static final Attributes.Name | EXTENSION_INSTALLATION | **Deprecated.** Extension mechanism is no longer supported. |
| static final Attributes.Name | EXTENSION_LIST | Name object for Extension-List manifest attribute used for the extension mechanism that is no longer supported. |
| | EXTENSION_NAME | |

| | | |
|---|---|---|
| static final Attributes.Name | | Name object for Extension-Name manifest attribute used for the extension mechanism that is no longer supported. |
| static final Attributes.Name | IMPLEMENTATION_TITLE | Name object for Implementation-Title manifest attribute used for package versioning. |
| static final Attributes.Name | IMPLEMENTATION_URL | **Deprecated.** Extension mechanism is no longer supported. |
| static final Attributes.Name | IMPLEMENTATION_VENDOR | Name object for Implementation-Vendor manifest attribute used for package versioning. |
| static final Attributes.Name | IMPLEMENTATION_VENDOR_ID | **Deprecated.** Extension mechanism is no longer supported. |
| static final Attributes.Name | IMPLEMENTATION_VERSION | Name object for Implementation-Version manifest attribute used for package versioning. |
| static final Attributes.Name | MAIN_CLASS | Name object for Main-Class manifest attribute used for launching applications packaged in JAR files. |
| static final Attributes.Name | MANIFEST_VERSION | Name object for Manifest-Version manifest attribute. |
| static final Attributes.Name | MULTI_RELEASE | Name object for Multi-Release manifest attribute that indicates this is a multi-release JAR file. |

| | | |
|---|---|---|
| static final Attributes.Name | SEALED | Name object for Sealed manifest attribute used for sealing. |
| static final Attributes.Name | SIGNATURE_VERSION | Name object for Signature-Version manifest attribute used when signing JAR files. |
| static final Attributes.Name | SPECIFICATION_TITLE | Name object for Specification-Title manifest attribute used for package versioning. |
| static final Attributes.Name | SPECIFICATION_VENDOR | Name object for Specification-Vendor manifest attribute used for package versioning. |
| static final Attributes.Name | SPECIFICATION_VERSION | Name object for Specification-Version manifest attribute used for package versioning. |

## *Constructor Summary*

**Constructors**

| Constructor | Description |
|---|---|
| Name(String name) | Constructs a new attribute name using the given string name. |

## *Method Summary*

**All Methods** | **Instance Methods**

| Modifier and Type | Method | Description |
|---|---|---|
| boolean | equals(Object o) | Compares this attribute name to another for equality. |
| int | hashCode() | Computes the hash value for this attribute name. |

| | | |
|---|---|---|
| String | **toString**() | Returns the attribute name as a String. |

**Methods declared in class Object**

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

## *Field Details*

### MANIFEST_VERSION

public static final Attributes.Name MANIFEST_VERSION

Name object for Manifest-Version manifest attribute. This attribute indicates the version number of the manifest standard to which a JAR file's manifest conforms.

**See Also:**

Manifest and Signature Specification

### SIGNATURE_VERSION

public static final Attributes.Name SIGNATURE_VERSION

Name object for Signature-Version manifest attribute used when signing JAR files.

**See Also:**

Manifest and Signature Specification

### CONTENT_TYPE

public static final Attributes.Name CONTENT_TYPE

Name object for Content-Type manifest attribute.

### CLASS_PATH

public static final Attributes.Name CLASS_PATH

Name object for Class-Path manifest attribute.

**See Also:**

JAR file specification

### MAIN_CLASS

public static final Attributes.Name MAIN_CLASS

Name object for `Main-Class` manifest attribute used for launching applications packaged in JAR files. The `Main-Class` attribute is used in conjunction with the `-jar` command-line option of the `java` application launcher.

### SEALED

```
public static final Attributes.Name SEALED
```

Name object for `Sealed` manifest attribute used for sealing.

**See Also:**

Package Sealing

### EXTENSION_LIST

```
public static final Attributes.Name EXTENSION_LIST
```

Name object for `Extension-List` manifest attribute used for the extension mechanism that is no longer supported.

### EXTENSION_NAME

```
public static final Attributes.Name EXTENSION_NAME
```

Name object for `Extension-Name` manifest attribute used for the extension mechanism that is no longer supported.

### EXTENSION_INSTALLATION

```
@Deprecated
public static final Attributes.Name EXTENSION_INSTALLATION
```

**Deprecated.**
*Extension mechanism is no longer supported.*

Name object for `Extension-Installation` manifest attribute.

### IMPLEMENTATION_TITLE

```
public static final Attributes.Name IMPLEMENTATION_TITLE
```

Name object for `Implementation-Title` manifest attribute used for package versioning.

### IMPLEMENTATION_VERSION

```
public static final Attributes.Name IMPLEMENTATION_VERSION
```

Name object for `Implementation-Version` manifest attribute used for package versioning.

### IMPLEMENTATION_VENDOR

```
public static final Attributes.Name IMPLEMENTATION_VENDOR
```

Name object for `Implementation-Vendor` manifest attribute used for package versioning.

### IMPLEMENTATION_VENDOR_ID

```
@Deprecated
public static final Attributes.Name IMPLEMENTATION_VENDOR_ID
```

**Deprecated.**
*Extension mechanism is no longer supported.*

Name object for `Implementation-Vendor-Id` manifest attribute.

### IMPLEMENTATION_URL

```
@Deprecated
public static final Attributes.Name IMPLEMENTATION_URL
```

**Deprecated.**
*Extension mechanism is no longer supported.*

Name object for `Implementation-URL` manifest attribute.

### SPECIFICATION_TITLE

```
public static final Attributes.Name SPECIFICATION_TITLE
```

Name object for `Specification-Title` manifest attribute used for package versioning.

### SPECIFICATION_VERSION

```
public static final Attributes.Name SPECIFICATION_VERSION
```

Name object for `Specification-Version` manifest attribute used for package versioning.

### SPECIFICATION_VENDOR

```
public static final Attributes.Name SPECIFICATION_VENDOR
```

Name object for `Specification-Vendor` manifest attribute used for package versioning.

### MULTI_RELEASE

`public static final Attributes.Name MULTI_RELEASE`

Name object for `Multi-Release` manifest attribute that indicates this is a multi-release JAR file.

**Since:**

9

## *Constructor Details*

### Name

`public Name(String name)`

Constructs a new attribute name using the given string name.

**Parameters:**

`name` - the attribute string name

**Throws:**

`IllegalArgumentException` - if the attribute name was invalid

`NullPointerException` - if the attribute name was null

## *Method Details*

### equals

`public boolean equals(Object o)`

Compares this attribute name to another for equality.

**Overrides:**

`equals` in class `Object`

**Parameters:**

`o` - the object to compare

**Returns:**

true if this attribute name is equal to the specified attribute object

**See Also:**

`Object.hashCode()`, `HashMap`

## hashCode

```
public int hashCode()
```

Computes the hash value for this attribute name.

**Overrides:**

`hashCode` in class `Object`

**Returns:**

a hash code value for this object

**See Also:**

`Object.equals(java.lang.Object)`,
`System.identityHashCode(Object)`

## toString

```
public String toString()
```

Returns the attribute name as a String.

**Overrides:**

`toString` in class `Object`

**Returns:**

a string representation of the object

---

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.