JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class JarEntry

java.lang.Object
  java.util.zip.ZipEntry
    java.util.jar.JarEntry

All Implemented Interfaces:

Cloneable

```
public class JarEntry
extends ZipEntry
```

This class is used to represent a JAR file entry.

Since:

1.2

Field Summary

Fields

Modifier and Type	Field	Description
static final int	CENATT	Central directory (CEN) header internal file attributes field offset.
static final int	CENATX	Central directory (CEN) header external file attributes field offset.
static final int	CENCOM	Central directory (CEN) header comment length field offset.
static final int	CENCRC	Central directory (CEN) header uncompressed file crc-32 value field offset.
static final int	CENDSK	Central directory (CEN) header disk number start field offset.
static final int	CENEXT	Central directory (CEN) header extra field length field offset.
static final int	CENFLG	

		Central directory (CEN) header encrypt, decrypt flags field offset.
`static final int`	**`CENHDR`**	Central directory (CEN) header size in bytes (including signature).
`static final int`	**`CENHOW`**	Central directory (CEN) header compression method field offset.
`static final int`	**`CENLEN`**	Central directory (CEN) header uncompressed size field offset.
`static final int`	**`CENNAM`**	Central directory (CEN) header filename length field offset.
`static final int`	**`CENOFF`**	Central directory (CEN) header LOC header offset field offset.
`static final long`	**`CENSIG`**	Central directory (CEN) header signature.
`static final int`	**`CENSIZ`**	Central directory (CEN) header compressed size field offset.
`static final int`	**`CENTIM`**	Central directory (CEN) header modification time field offset.
`static final int`	**`CENVEM`**	Central directory (CEN) header version made by field offset.
`static final int`	**`CENVER`**	Central directory (CEN) header version needed to extract field offset.
`static final int`	**`ENDCOM`**	End of central directory (END) header ZIP file comment length field offset.

`static final int`	**`ENDHDR`**	End of central directory (END) header size in bytes (including signature).
`static final int`	**`ENDOFF`**	End of central directory (END) header offset for the first CEN header field offset.
`static final long`	**`ENDSIG`**	End of central directory (END) header signature.
`static final int`	**`ENDSIZ`**	End of central directory (END) header central directory size in bytes field offset.
`static final int`	**`ENDSUB`**	End of central directory (END) header number of entries on this disk field offset.
`static final int`	**`ENDTOT`**	End of central directory (END) header total number of entries field offset.
`static final int`	**`EXTCRC`**	Extra local (EXT) header uncompressed file crc-32 value field offset.
`static final int`	**`EXTHDR`**	Extra local (EXT) header size in bytes (including signature).
`static final int`	**`EXTLEN`**	Extra local (EXT) header uncompressed size field offset.
`static final long`	**`EXTSIG`**	Extra local (EXT) header signature.
`static final int`	**`EXTSIZ`**	Extra local (EXT) header compressed size field offset.

static final int	**LOCCRC**	Local file (LOC) header uncompressed file crc-32 value field offset.
static final int	**LOCEXT**	Local file (LOC) header extra field length field offset.
static final int	**LOCFLG**	Local file (LOC) header general purpose bit flag field offset.
static final int	**LOCHDR**	Local file (LOC) header size in bytes (including signature).
static final int	**LOCHOW**	Local file (LOC) header compression method field offset.
static final int	**LOCLEN**	Local file (LOC) header uncompressed size field offset.
static final int	**LOCNAM**	Local file (LOC) header filename length field offset.
static final long	**LOCSIG**	Local file (LOC) header signature.
static final int	**LOCSIZ**	Local file (LOC) header compressed size field offset.
static final int	**LOCTIM**	Local file (LOC) header modification time field offset.
static final int	**LOCVER**	Local file (LOC) header version needed to extract field offset.

Fields declared in class ZipEntry

DEFLATED, STORED

Constructor Summary

Constructors

Constructor	Description
`JarEntry(String name)`	Creates a new `JarEntry` for the specified JAR file entry name.
`JarEntry(JarEntry je)`	Creates a new `JarEntry` with fields taken from the specified `JarEntry` object.
`JarEntry(ZipEntry ze)`	Creates a new `JarEntry` with fields taken from the specified `ZipEntry` object.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
`Attributes`	`getAttributes()`	Returns the `Manifest` `Attributes` for this entry, or `null` if none.
`Certificate[]`	`getCertificates()`	Returns the `Certificate` objects for this entry, or `null` if none.
`CodeSigner[]`	`getCodeSigners()`	Returns the `CodeSigner` objects for this entry, or `null` if none.
`String`	`getRealName()`	Returns the real name of this `JarEntry`.

Methods declared in class ZipEntry

`clone`, `getComment`, `getCompressedSize`, `getCrc`, `getCreationTime`, `getExtra`, `getLastAccessTime`, `getLastModifiedTime`, `getMethod`, `getName`, `getSize`, `getTime`, `getTimeLocal`, `hashCode`, `isDirectory`, `setComment`, `setCompressedSize`, `setCrc`, `setCreationTime`, `setExtra`, `setLastAccessTime`, `setLastModifiedTime`, `setMethod`, `setSize`, `setTime`, `setTimeLocal`, `toString`

Methods declared in class Object

`equals`, `finalize`, `getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Field Details

LOCSIG

`static final long LOCSIG`

Local file (LOC) header signature.

See Also:

Constant Field Values

EXTSIG

`static final long EXTSIG`

Extra local (EXT) header signature.

See Also:

Constant Field Values

CENSIG

`static final long CENSIG`

Central directory (CEN) header signature.

See Also:

Constant Field Values

ENDSIG

`static final long ENDSIG`

End of central directory (END) header signature.

See Also:

Constant Field Values

LOCHDR

`static final int LOCHDR`

Local file (LOC) header size in bytes (including signature).

See Also:

Constant Field Values

EXTHDR

`static final int EXTHDR`

Extra local (EXT) header size in bytes (including signature).

See Also:

Constant Field Values

CENHDR

`static final int CENHDR`

Central directory (CEN) header size in bytes (including signature).

See Also:

Constant Field Values

ENDHDR

`static final int ENDHDR`

End of central directory (END) header size in bytes (including signature).

See Also:

Constant Field Values

LOCVER

`static final int LOCVER`

Local file (LOC) header version needed to extract field offset.

See Also:

Constant Field Values

LOCFLG

`static final int LOCFLG`

Local file (LOC) header general purpose bit flag field offset.

See Also:

Constant Field Values

LOCHOW

`static final int LOCHOW`

Local file (LOC) header compression method field offset.

See Also:

Constant Field Values

LOCTIM

`static final int LOCTIM`

Local file (LOC) header modification time field offset.

See Also:

Constant Field Values

LOCCRC

`static final int LOCCRC`

Local file (LOC) header uncompressed file crc-32 value field offset.

See Also:

Constant Field Values

LOCSIZ

`static final int LOCSIZ`

Local file (LOC) header compressed size field offset.

See Also:

Constant Field Values

LOCLEN

`static final int LOCLEN`

Local file (LOC) header uncompressed size field offset.

See Also:

Constant Field Values

LOCNAM

`static final int LOCNAM`

Local file (LOC) header filename length field offset.

See Also:

Constant Field Values

LOCEXT

```
static final int LOCEXT
```

Local file (LOC) header extra field length field offset.

See Also:

Constant Field Values

EXTCRC

```
static final int EXTCRC
```

Extra local (EXT) header uncompressed file crc-32 value field offset.

See Also:

Constant Field Values

EXTSIZ

```
static final int EXTSIZ
```

Extra local (EXT) header compressed size field offset.

See Also:

Constant Field Values

EXTLEN

```
static final int EXTLEN
```

Extra local (EXT) header uncompressed size field offset.

See Also:

Constant Field Values

CENVEM

```
static final int CENVEM
```

Central directory (CEN) header version made by field offset.

See Also:

Constant Field Values

CENVER

```
static final int CENVER
```

Central directory (CEN) header version needed to extract field offset.

See Also:

Constant Field Values

CENFLG

`static final int CENFLG`

Central directory (CEN) header encrypt, decrypt flags field offset.

See Also:

Constant Field Values

CENHOW

`static final int CENHOW`

Central directory (CEN) header compression method field offset.

See Also:

Constant Field Values

CENTIM

`static final int CENTIM`

Central directory (CEN) header modification time field offset.

See Also:

Constant Field Values

CENCRC

`static final int CENCRC`

Central directory (CEN) header uncompressed file crc-32 value field offset.

See Also:

Constant Field Values

CENSIZ

`static final int CENSIZ`

Central directory (CEN) header compressed size field offset.

See Also:

Constant Field Values

CENLEN

```
static final int CENLEN
```

Central directory (CEN) header uncompressed size field offset.

See Also:

Constant Field Values

CENNAM

```
static final int CENNAM
```

Central directory (CEN) header filename length field offset.

See Also:

Constant Field Values

CENEXT

```
static final int CENEXT
```

Central directory (CEN) header extra field length field offset.

See Also:

Constant Field Values

CENCOM

```
static final int CENCOM
```

Central directory (CEN) header comment length field offset.

See Also:

Constant Field Values

CENDSK

```
static final int CENDSK
```

Central directory (CEN) header disk number start field offset.

See Also:

Constant Field Values

CENATT

```
static final int CENATT
```

Central directory (CEN) header internal file attributes field offset.

See Also:

Constant Field Values

CENATX

`static final int CENATX`

Central directory (CEN) header external file attributes field offset.

See Also:

Constant Field Values

CENOFF

`static final int CENOFF`

Central directory (CEN) header LOC header offset field offset.

See Also:

Constant Field Values

ENDSUB

`static final int ENDSUB`

End of central directory (END) header number of entries on this disk field offset.

See Also:

Constant Field Values

ENDTOT

`static final int ENDTOT`

End of central directory (END) header total number of entries field offset.

See Also:

Constant Field Values

ENDSIZ

`static final int ENDSIZ`

End of central directory (END) header central directory size in bytes field offset.

See Also:

Constant Field Values

ENDOFF

```
static final int ENDOFF
```

End of central directory (END) header offset for the first CEN header field offset.

See Also:

Constant Field Values

ENDCOM

```
static final int ENDCOM
```

End of central directory (END) header ZIP file comment length field offset.

See Also:

Constant Field Values

Constructor Details

JarEntry

```
public JarEntry(String name)
```

Creates a new `JarEntry` for the specified JAR file entry name.

Parameters:

`name` - the JAR file entry name

Throws:

`NullPointerException` - if the entry name is `null`

`IllegalArgumentException` - if the entry name is longer than 0xFFFF bytes.

JarEntry

```
public JarEntry(ZipEntry ze)
```

Creates a new `JarEntry` with fields taken from the specified `ZipEntry` object.

Parameters:

`ze` - the `ZipEntry` object to create the `JarEntry` from

Throws:

`NullPointerException` - if `ze` is null

JarEntry

```
public JarEntry(JarEntry je)
```

Creates a new `JarEntry` with fields taken from the specified `JarEntry` object.

Parameters:

`je` - the `JarEntry` to copy

Throws:

`NullPointerException` - if `je` is null

Method Details

getAttributes

```
public Attributes getAttributes()
                           throws IOException
```

Returns the `Manifest` `Attributes` for this entry, or `null` if none.

Returns:

the `Manifest` `Attributes` for this entry, or `null` if none

Throws:

`IOException` - if an I/O error has occurred

getCertificates

```
public Certificate[] getCertificates()
```

Returns the `Certificate` objects for this entry, or `null` if none. This method can only be called once the `JarEntry` has been completely verified by reading from the entry input stream until the end of the stream has been reached. Otherwise, this method will return `null`.

It is recommended to use the `getCodeSigners()` method instead, which returns an array of `CodeSigners`.

The returned certificate array comprises all the signer certificates that were used to verify this entry. Each signer certificate is followed by its supporting certificate chain (which may be empty). Each signer certificate and its supporting certificate chain are ordered bottom-to-top (i.e., with the signer certificate first and the (root) certificate authority last).

API Note:

The verification process does not include validating or establishing trust in the
code signers. A caller should perform additional checks, such as using a `CertPathValidator` to validate each signer's certificate chain, and determining whether to trust the entry signed by the signers.

Implementation Requirements:

If non-null, this implementation returns a new array each time this method is invoked.

Returns:

the `Certificate` objects for this entry, or `null` if none.

getCodeSigners

```
public CodeSigner[] getCodeSigners()
```

Returns the `CodeSigner` objects for this entry, or `null` if none. This method can only be called once the `JarEntry` has been completely verified by reading from the entry input stream until the end of the stream has been reached. Otherwise, this method will return `null`.

The returned array comprises all the code signers that have signed this entry.

API Note:

The verification process does not include validating or establishing trust in the
code signers. A caller should perform additional checks, such as using a `CertPathValidator` to validate each signer's certificate chain, and determining whether to trust the entry signed by the signers.

Implementation Requirements:

If non-null, this implementation returns a new array each time this method is invoked.

Returns:

the `CodeSigner` objects for this entry, or `null` if none.

Since:

1.5

getRealName

```
public String getRealName()
```

Returns the real name of this `JarEntry`. If this `JarEntry` is an entry of a multi-release jar file and the `JarFile` is configured to be processed as such, the name returned by this method is the path name of the versioned entry that the `JarEntry` represents, rather than the path name of the base entry that `ZipEntry.getName()` returns. If the `JarEntry` does not represent a versioned entry of a multi-release `JarFile` or the `JarFile` is not configured for processing a multi-release jar file, this method returns the same name that `ZipEntry.getName()` returns.

Returns:

the real name of the JarEntry

Since:

10

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.