JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class Manifest

java.lang.Object
    java.util.jar.Manifest

All Implemented Interfaces:

Cloneable

```
public class Manifest
extends Object
implements Cloneable
```

The Manifest class is used to maintain Manifest entry names and their associated Attributes. There are main Manifest Attributes as well as per-entry Attributes. For information on the Manifest format, please see the Manifest format specification.

Unless otherwise noted, passing a `null` argument to a constructor or method in this class will cause a `NullPointerException` to be thrown.

Since:

1.2

External Specifications

JAR File Specification

See Also:

Attributes

Constructor Summary

Constructors

Constructor	Description
`Manifest()`	Constructs a new, empty Manifest.
`Manifest(InputStream is)`	Constructs a new Manifest from the specified input stream.
`Manifest(Manifest man)`	Constructs a new Manifest that is a copy of the specified Manifest.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description

void	**clear**()	Clears the main Attributes as well as the entries in this Manifest.
Object	**clone**()	Returns a shallow copy of this Manifest.
boolean	**equals**(Object o)	Returns true if the specified Object is also a Manifest and has the same main Attributes and entries.
Attributes	**getAttributes** (String name)	Returns the Attributes for the specified entry name.
Map<String, Attributes>	**getEntries**()	Returns a Map of the entries contained in this Manifest.
Attributes	**getMainAttributes**()	Returns the main Attributes for the Manifest.
int	**hashCode**()	Returns the hash code for this Manifest.
void	**read**(InputStream is)	Reads the Manifest from the specified InputStream.
void	**write**(OutputStream out)	Writes the Manifest to the specified OutputStream.

Methods declared in class Object

finalize, getClass, notify, notifyAll, toString, wait, wait, wait

Constructor Details

Manifest

```
public Manifest()
```

Constructs a new, empty Manifest.

Manifest

```
public Manifest(InputStream is)
         throws IOException
```

Constructs a new Manifest from the specified input stream.

Parameters:

`is` - the input stream containing manifest data

Throws:

`IOException` - if an I/O error has occurred

Manifest

```
public Manifest(Manifest man)
```

Constructs a new Manifest that is a copy of the specified Manifest.

Parameters:

`man` - the Manifest to copy

Method Details

getMainAttributes

```
public Attributes getMainAttributes()
```

Returns the main Attributes for the Manifest.

Returns:

the main Attributes for the Manifest

getEntries

```
public Map<String, Attributes> getEntries()
```

Returns a Map of the entries contained in this Manifest. Each entry is represented by a String name (key) and associated Attributes (value). The Map permits the `null` key, but no entry with a null key is created by `read(InputStream)`, nor is such an entry written by using `write(OutputStream)`.

Returns:

a Map of the entries contained in this Manifest

getAttributes

```
public Attributes getAttributes(String name)
```

Returns the Attributes for the specified entry name. This method is defined as:

```
     return (Attributes)getEntries().get(name)
```

Though `null` is a valid `name`, when `getAttributes(null)` is invoked on a `Manifest` obtained from a jar file, `null` will be returned. While jar files themselves do not allow `null`-named attributes, it is possible to invoke `getEntries()` on a `Manifest`, and on that result, invoke `put` with a null key and an arbitrary value. Subsequent invocations of `getAttributes(null)` will return the just-`put` value.

Note that this method does not return the manifest's main attributes; see `getMainAttributes()`.

Parameters:

`name` - entry name

Returns:

the Attributes for the specified entry name

clear

```
public void clear()
```

Clears the main Attributes as well as the entries in this Manifest.

write

```
public void write(OutputStream out)
           throws IOException
```

Writes the Manifest to the specified OutputStream. Attributes.Name.MANIFEST_VERSION must be set in MainAttributes prior to invoking this method.

Parameters:

`out` - the output stream

Throws:

`IOException` - if an I/O error has occurred

See Also:

`getMainAttributes()`

read

```
public void read(InputStream is)
          throws IOException
```

Reads the Manifest from the specified InputStream. The entry names and attributes read will be merged in with the current manifest entries.

Parameters:

`is` - the input stream

Throws:

`IOException` - if an I/O error has occurred

equals

```
public boolean equals(Object o)
```

Returns true if the specified Object is also a Manifest and has the same main Attributes and entries.

Overrides:

`equals` in class `Object`

Parameters:

`o` - the object to be compared

Returns:

true if the specified Object is also a Manifest and has the same main Attributes and entries

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public int hashCode()
```

Returns the hash code for this Manifest.

Overrides:

`hashCode` in class `Object`

Returns:

a hash code value for this object

See Also:

`Object.equals(java.lang.Object)`,
`System.identityHashCode(Object)`

clone

`public Object clone()`

Returns a shallow copy of this Manifest. The shallow copy is implemented as follows:

```
public Object clone() { return new Manifest(this); }
```

Overrides:

`clone` in class `Object`

Returns:

a shallow copy of this Manifest

See Also:

`Cloneable`

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.