JavaScript is disabled on your browser.

**Java SE 27 & JDK 27**

# Class ErrorManager

java.lang.Object
    java.util.logging.ErrorManager

---

```
public class ErrorManager
extends Object
```

ErrorManager objects can be attached to Handlers to process any error that occurs on a Handler during Logging.

When processing logging output, if a Handler encounters problems then rather than throwing an Exception back to the issuer of the logging call (who is unlikely to be interested) the Handler should call its associated ErrorManager.

**Since:**

1.4

## *Field Summary*

**Fields**

| Modifier and Type | Field | Description |
|---|---|---|
| static final int | CLOSE_FAILURE | CLOSE_FAILURE is used when a close of an output stream fails. |
| static final int | FLUSH_FAILURE | FLUSH_FAILURE is used when a flush to an output stream fails. |
| static final int | FORMAT_FAILURE | FORMAT_FAILURE is used when formatting fails for any reason. |
| static final int | GENERIC_FAILURE | GENERIC_FAILURE is used for failure that don't fit into one of the other categories. |
| static final int | OPEN_FAILURE | OPEN_FAILURE is used when an open of an output stream fails. |
| static final int | WRITE_FAILURE | WRITE_FAILURE is used when a write to an output stream fails. |

## Constructor Summary

| Constructors | |
|---|---|
| **Constructor** | **Description** |
| `ErrorManager()` | Create an `ErrorManager`. |

## Method Summary

| All Methods | Instance Methods | |
|---|---|---|
| **Modifier and Type** | **Method** | **Description** |
| `void` | `error(String msg, Exception ex, int code)` | The error method is called when a Handler failure occurs. |

**Methods declared in class Object**

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Field Details

### GENERIC_FAILURE

```
public static final int GENERIC_FAILURE
```

GENERIC_FAILURE is used for failure that don't fit into one of the other categories.

**See Also:**

Constant Field Values

### WRITE_FAILURE

```
public static final int WRITE_FAILURE
```

WRITE_FAILURE is used when a write to an output stream fails.

**See Also:**

Constant Field Values

### FLUSH_FAILURE

```
public static final int FLUSH_FAILURE
```

FLUSH_FAILURE is used when a flush to an output stream fails.

**See Also:**

Constant Field Values

### CLOSE_FAILURE

```
public static final int CLOSE_FAILURE
```

CLOSE_FAILURE is used when a close of an output stream fails.

**See Also:**

Constant Field Values

### OPEN_FAILURE

```
public static final int OPEN_FAILURE
```

OPEN_FAILURE is used when an open of an output stream fails.

**See Also:**

Constant Field Values

### FORMAT_FAILURE

```
public static final int FORMAT_FAILURE
```

FORMAT_FAILURE is used when formatting fails for any reason.

**See Also:**

Constant Field Values

## *Constructor Details*

### ErrorManager

```
public ErrorManager()
```

Create an `ErrorManager`.

## *Method Details*

### error

```
public void error(String msg,
                  Exception ex,
                  int code)
```

The error method is called when a Handler failure occurs.

This method may be overridden in subclasses. The default behavior in this base class is that the first call is reported to System.err, and subsequent calls are ignored.

**Parameters:**

`msg` - a descriptive string (may be null)

`ex` - an exception (may be null)

`code` - an error code defined in ErrorManager

---

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.