JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface LoggingMXBean

```
@Deprecated(since="9")
public interface LoggingMXBean
```

Deprecated.
LoggingMXBean is no longer a platform MXBean and is replaced with PlatformLoggingMXBean. It will not register in the platform MBeanServer. Use ManagementFactory.getPlatformMXBean(PlatformLoggingMXBean.class) instead.

The management interface for the logging facility.
`java.lang.management.PlatformLoggingMXBean` is the management interface for logging facility registered in the `platform MBeanServer`. It is recommended to use the `PlatformLoggingMXBean` obtained via the `ManagementFactory.getPlatformMXBean(PlatformLoggingMXBean.class)` method.

Since:

1.5

See Also:

`PlatformLoggingMXBean`

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
`String`	**`getLoggerLevel`**`(String loggerName)`	**Deprecated.** Gets the name of the log level associated with the specified logger.
`List<String>`	**`getLoggerNames`**`()`	**Deprecated.** Returns the list of currently registered logger names.
`String`	**`getParentLoggerName`**`(String loggerName)`	**Deprecated.** Returns the name of the parent for the specified logger.

void	**setLoggerLevel**(String loggerName, String levelName)	**Deprecated.** Sets the specified logger to the specified new level.

Method Details

getLoggerNames

`List<String> getLoggerNames()`

Deprecated.

Returns the list of currently registered logger names. This method calls `LogManager.getLoggerNames()` and returns a list of the logger names.

Returns:

A list of `String` each of which is a currently registered `Logger` name.

getLoggerLevel

`String getLoggerLevel(String loggerName)`

Deprecated.

Gets the name of the log level associated with the specified logger. If the specified logger does not exist, `null` is returned. This method first finds the logger of the given name and then returns the name of the log level by calling:

```
Logger.getLevel().getName();
```

If the `Level` of the specified logger is `null`, which means that this logger's effective level is inherited from its parent, an empty string will be returned.

Parameters:

`loggerName` - The name of the `Logger` to be retrieved.

Returns:

The name of the log level of the specified logger; or an empty string if the log level of the specified logger is `null`. If the specified logger does not exist, `null` is returned.

See Also:

`Logger.getLevel()`

setLoggerLevel

```
void setLoggerLevel(String loggerName,
                    String levelName)
```

Deprecated.

Sets the specified logger to the specified new level. If the `levelName` is not `null`, the level of the specified logger is set to the parsed `Level` matching the `levelName`. If the `levelName` is `null`, the level of the specified logger is set to `null` and the effective level of the logger is inherited from its nearest ancestor with a specific (non-null) level value.

Parameters:

`loggerName` - The name of the `Logger` to be set. Must be non-null.

`levelName` - The name of the level to set on the specified logger, or `null` if setting the level to inherit from its nearest ancestor.

Throws:

`IllegalArgumentException` - if the specified logger does not exist, or `levelName` is not a valid level name.

See Also:

`Logger.setLevel(Level)`

getParentLoggerName

```
String getParentLoggerName(String loggerName)
```

Deprecated.

Returns the name of the parent for the specified logger. If the specified logger does not exist, `null` is returned. If the specified logger is the root `Logger` in the namespace, the result will be an empty string.

Parameters:

`loggerName` - The name of a `Logger`.

Returns:

the name of the nearest existing parent logger; an empty string if the specified logger is the root logger. If the specified logger does not exist, `null` is returned.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.

Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.