JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface NodeChangeListener

All Superinterfaces:

EventListener

```
public interface NodeChangeListener
extends EventListener
```

A listener for receiving preference node change events.

Since:

1.4

See Also:

Preferences, NodeChangeEvent, PreferenceChangeListener

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
void	childAdded (NodeChangeEvent evt)	This method gets called when a child node is added.
void	childRemoved (NodeChangeEvent evt)	This method gets called when a child node is removed.

Method Details

childAdded

```
void childAdded(NodeChangeEvent evt)
```

This method gets called when a child node is added.

Parameters:

evt - A node change event object describing the parent and child node.

childRemoved

```
void childRemoved(NodeChangeEvent evt)
```

This method gets called when a child node is removed.

Parameters:

`evt` - A node change event object describing the parent and child node.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.